


SuperServer 6019U-TN4RT (Complete System Only)



Key Features

- Virtualization
- Cloud Computing
- High End Enterprise Server

1. Dual socket P (LGA 3647) supports Intel® Xeon® Scalable Processors, Dual UPI up to 10.4GT/s
2. Up to 3TB ECC 3DS LRDIMM or RDIMM, up to DDR4-2666MHz; 24 DIMM slots
3. 2 PCI-E 3.0 x16 slots (FH, 10.5" L), 2 PCI-E 3.0 x8 slots (1 LP, 1 internal LP)
4. 2x 10GBase-T Ethernet ports
5. 4 Hot-swap 3.5" drive bays: 4 NVMe/SATA3 hybrid ports; 2 internal M.2 (1 SATA3, 1 NVMe)
6. 8 Heavy duty fans w/ optimal fan speed control
7. 750W Redundant Power Supplies Platinum Level (94%+)

Due to the complexity of integration, this product is sold as completely assembled systems only (including but not limited to CPUs, memory, and HDDs). Please contact your Supermicro sales rep for special requirements.

[▶ Drivers & Utilities](#)
[▶ BIOS](#)
[▶ IPMI](#)
[▶ Tested Memory](#)
[▶ NVMe Options](#)
[▶ OS Certification Matrix](#)
[▶ Drive Options](#)

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

Specifications

Product SKUs	
SYS-6019U-TN4RT	▪ SuperServer 6019U-TN4RT (Black)
Motherboard	
Super X11DPU	
Processor/Cache	
CPU	<ul style="list-style-type: none"> ▪ Dual Socket P (LGA 3647) ▪ Intel® Xeon® Scalable Processors, Dual UPI up to 10.4GT/s ▪ Support CPU TDP 70-205W
Cores	▪ Up to 28 Cores with Intel® HT Technology
System Memory	
Memory Capacity	<ul style="list-style-type: none"> ▪ 24 DIMM slots ▪ Up to 3TB ECC 3DS LRDIMM, 3TB ECC RDIMM, DDR4 up to 2666MHz
Memory Type	▪ 2666/2400/2133MHz ECC DDR4 SDRAM

Chassis	
Form Factor	▪ 1U Rackmount
Model	▪ CSE-819UTQ4-R751-T
Dimensions and Weight	
Height	▪ 1.7" (43mm)
Width	▪ 17.2" (437mm)
Depth	▪ 29" (737mm)
Weight	<ul style="list-style-type: none"> ▪ Net Weight: 26 lbs (11.8 kg) ▪ Gross Weight: 41 lbs (18.6 kg)
Available Color	▪ Black
Front Panel	
Buttons	<ul style="list-style-type: none"> ▪ Power On/Off button ▪ System Reset button
LEDs	<ul style="list-style-type: none"> ▪ Power LED ▪ Hard drive activity LED ▪ Network activity LEDs ▪ System Overheat LED / Fan fail LED / UID LED

On-Board Devices

Chipset	▪ Intel® C621 chipset
SATA	▪ SATA3 (6Gbps); RAID 0, 1, 5, 10
Network Connectivity	▪ 2x 10GBase-T ports via (AOC-UR-I2XT)
IPMI	▪ Support for Intelligent Platform Management Interface v.2.0 ▪ IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Graphics	▪ ASPEED AST2500 BMC

Input / Output

SATA/NVMe	▪ 4 SATA3 (6Gbps)/NVMe ports
LAN	▪ 2 RJ45 10GBase-T Ethernet ports ▪ 1 RJ45 Dedicated IPMI LAN port
USB	▪ 3 USB 3.0 ports (2 rear, 1 Type A)
Video	▪ 2 VGA ports (1 rear, 1 onboard)
Serial Port	▪ 1 Serial header
DOM	▪ 2 SATA <u>DOM</u> (Disk on Module) support with embedded power

System BIOS

BIOS Type	▪ AMI 32Mb SPI Flash ROM
-----------	--------------------------

Management

Software	▪ Intel® Node Manager ▪ IPMI 2.0 ▪ KVM with dedicated LAN ▪ NMI ▪ SSM , SPM , SUM ▪ SuperDoctor® 5
Power Configurations	▪ ACPI Power Management

PC Health Monitoring

CPU	▪ Monitors for CPU Cores, Chipset Voltages, Memory. ▪ 4+1 Phase-switching voltage regulator
FAN	▪ Fans with tachometer monitoring ▪ Status monitor for speed control ▪ Pulse Width Modulated (PWM) fan connectors
Temperature	▪ Monitoring for CPU and chassis environment ▪ Thermal Control for fan connectors

Expansion Slots

	▪ 2 PCI-E 3.0 x16 (Full-height, 10.5" L) ▪ 2 PCI-E 3.0 x8 (1 LP, 1 internal LP)
PCI-Express	(Both CPUs need to be installed for full access to PCI-E slots and onboard controllers. See manual block diagram and AOC Support for details.)

Drive Bays

Hot-swap	▪ 4 Hot-swap 3.5" drive bays: 4 NVMe/SATA3 hybrid ports (optional SAS3 via AOC)
M.2	▪ 1 M.2 NVMe (2242/2260/2280*/22110*) ▪ 1 M.2 SATA (2242/2260/2280*/22110*) via optional SATA cable * Not supported if installing both NVMe & SATA M.2

System Cooling

Fans	▪ 8 Heavy duty fans with optimal fan speed control
Air Shroud	▪ 1 Air Shroud

Power Supply

750W Redundant AC-DC Power Supplies, +12V/+12Vsb output	
AC Input	▪ 100-127Vac, 50-60Hz ▪ 200-240Vac, 50-60Hz
+12V	▪ Max: 62.5A & Min: 0A (100Vac-127Vac) ▪ Max: 62.5A & Min: 0A (200Vac-240Vac)
12V SB	▪ Max: 2.1A ▪ Min: 0A

Certification	  Platinum Level [Test Report]
---------------	---

Operating Environment

RoHS	▪ RoHS Compliant
Environmental Spec.	▪ Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) ▪ Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) ▪ Operating Relative Humidity: 8% to 90% (non-condensing) ▪ Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11DPU	1	Super X11DPU Motherboard
	CSE-819UTQ4-R751-T	1	CSE-819UTQ4-R751-T Chassis
Add-on Card / Module	AOC-UR-I2XT	1	1U Ultra Riser based on Intel X540 controller with 2 10Gbase-T ports and 1 internal PCI-E x8 3.0 slot
Backplane	BPN-SAS3-815TQ-N4	1	4-port 1U SAS3 12Gbps Hybrid backplane, support up to 4x 3.5-inch SAS3/SATA3/NVMe Storage Devices
Cable 1	CBL-PWEX-0650	1	8 pin female to 2x RA(Right Angle) big 4 pin female power, 47/62CM, 18AWG,RoHS/REACH
Cable 2	CBL-SAST-0819	4	OCuLink v 1.0,INT,PCIe NVMe SSD, 65CM,34AWG,RoHS/REACH
Cable 3	CBL-SAST-0880	1	MINI SAS(RA-RS EXIT)-4 SATA,INT,55/55/55/55CM,55CM SB,30AWG
FAN 1	FAN-0101L4	4	40x56,4 Pin PWM,Primary for SC809,111, Sec.for SC816,819,808
Drive Tray(s)	MCP-220-00138-0B	4	Black gen-5.5 tool-less NVMe 3.5-to-2.5 drive tray, Orange tab
Rear Window	MCP-240-81909-0N	1	Ultra I/O Rear Window for SC819U, 119U-T tool-less chassis(i2XT)
Air Shroud	MCP-310-81910-0N	1	Plastic air shroud for SC819U, 119U (X11 24DIMM, left side)
Riser Card	RSC-R1UW-2E16	1	RSC-R1UW-2E16-O-P
Riser Card	RSC-UMR-8	1	1U Ultra RHS Riser Card with 1 PCIE/SATA Hybrid M.2 & 1 PCIE X8,,HF,RoHS
Heatsink / Retention	SNK-P0067PS	2	1U Passive CPU Heat Sink for X11 Purley Platform Equipped with a Narrow Retention Mechanism
Power Supply	PWS-751P-1R	2	1U 750W Redundant Platinum Single Output Power Supply w/Pmbus W73.5xH40xL203mm,RoHS/REACH

Optional Parts List

	Part Number	Qty	Description
Storage Control Card and Cable for SAS3 Drive Bays	AOC-S3008L-L8e & 1x CBL-SAST-0948	-	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 122HDD, HBA
	AOC-S3008L-L8i & 1x CBL-SAST-0948	-	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 63HDD, RAID 0,1,1E
	AOC-S3108L-H8iR & 1x CBL-SAST-0948	-	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60
Network Card(s)	AOC-S40G-i2Q	-	Standard LP 2-port 40GbE controller, based on Intel Fortville XL710
	AOC-SGP-i2	-	Standard LP, 2x GbE RJ45, PCI-E x4, Intel i350AM2
	AOC-SGP-i4	-	Standard LP, 4x GbE RJ45, PCI-E x4, Intel i350
	AOC-STG-b4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom BCM57840S
	AOC-STGN-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel 82599ES
	AOC-STGN-i1S	-	Standard LP, 1x 10GbE SFP+, PCI-E x8, Intel 82599EN
	AOC-STG-i2T	-	Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel X540
	AOC-STG-i2	-	Standard LP, 2x 10GbE CX4, PCI-E x8, Intel 82598EB
CachVault(s)	BTR-CV3108-1U1	-	CacheVault for Broadcom 3108 with Supercap mounting in 1U 40x56 fan tray
	BTR-TFM8G-LSICVM02 & BKT-BBU-BRACKET-05	-	CacheVault for Broadcom 3108; Supercap mounting bracket for PCI-E location
	BTR-TFM8G-LSICVM02 & MCP-240-00127-0N	-	CacheVault for Broadcom 3108; Supercap mounting bracket for 2.5" HDD location
Hot-swap 3.5" to 2.5" Hard Disk Drive Tray	MCP-220-00043-0N	-	Black hot-swap 3.5" to 2.5" HDD tray
Global Services & Support	OS4HR3/2/1	-	3/2/1-year onsite 24x7x4 service
	OSNBD3/2/1	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)