


# SuperServer 2029U-E1CRT (Complete System Only)



Due to the complexity of integration, this product is sold as completely assembled systems only (with minimum 2 CPU and 4 DIMM). Please contact your Supermicro sales rep for special requirements.

[Drivers & Utilities](#) | [BIOS](#) | [IPMI](#) | [Tested Memory](#) | [NVMe Options](#) | [OS Certification Matrix](#) | [Drive Options](#)

### Key Features

- Flexible Networking Options

- Dual socket P (LGA 3647) supports Intel® Xeon® Scalable Processors, Dual UPI up to 10.4GT/s
- Up to 3TB ECC 3DS LRDIMM or RDIMM, up to DDR4-2666MHz; 24 DIMM slots
- 1 PCI-E 3.0 x16 slot (FH, 10.5" L), 5 PCI-E 3.0 x8 slots (FH, 10.5" L), 1 PCI-E 3.0 x8 slot (LP), 1 PCI-E 3.0 x8 slot (internal LP)
- 2x 10GBase-T LAN ports via Intel X540
- 24 Hot-swap 2.5" drive bays: 24 SAS3 via opt. AOC (4 hybrid ports - opt. 4 NVMe)
- 4 Heavy duty 8cm PWM fans
- 1000W Redundant Power Supplies Titanium Level (96%)

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

### Specifications

#### Product SKUs

SYS-2029U-E1CRT	SuperServer 2029U-E1CRT (Black)
-----------------	---------------------------------

#### Motherboard

Super X11DPU

#### Processor/Cache

CPU	<ul style="list-style-type: none"> <li>Dual Socket P (LGA 3647)</li> <li>Intel® Xeon® Scalable Processors, Dual UPI up to 10.4GT/s</li> <li>Support CPU TDP 70-205W</li> </ul>
Cores	Up to 28 Cores with Intel® HT Technology

#### System Memory

Memory Capacity	<ul style="list-style-type: none"> <li>24 DIMM slots</li> <li>Up to 3TB 3DS ECC LRDIMM, 3TB ECC RDIMM, DDR4 up to 2666MHz</li> </ul>
Memory Type	2666/2400/2133MHz ECC DDR4 RDIMM, LRDIMM

#### Chassis

Form Factor	2U Rackmount
Model	CSE-219U2E1C4-R1K02-T

#### Dimensions and Weight

Width	17.2" (437mm)
Height	3.5" (89mm)
Depth	27.76" (705.3mm)
Weight	<ul style="list-style-type: none"> <li>Net Weight: 36 lbs (16.4 kg)</li> <li>Gross Weight: 72 lbs (32.7 kg)</li> </ul>
Available Colors	Black

#### Front Panel

Buttons	<ul style="list-style-type: none"> <li>Power On/Off button</li> <li>System Reset button</li> </ul>
LEDs	<ul style="list-style-type: none"> <li>Power status LED</li> <li>HDD activity LED</li> <li>Network activity LEDs</li> <li>System information (overheat/UID) LED</li> </ul>

On-Board Devices	
Chipset	<ul style="list-style-type: none"> <li>Intel® C621 chipset</li> </ul>
SAS	<ul style="list-style-type: none"> <li>SAS3 (12Gbps) via expander + Broadcom 3108/3008 AOC</li> </ul>
Network Connectivity	<ul style="list-style-type: none"> <li>2x 10GBase-T ports via Intel® X540 (AOC-2UR68-i2XT)</li> </ul>
IPMI	<ul style="list-style-type: none"> <li>Support for Intelligent Platform Management Interface v.2.0</li> <li>IPMI 2.0 with virtual media over LAN and KVM-over-LAN support</li> </ul>
Graphics	<ul style="list-style-type: none"> <li>ASPEED AST2500 BMC</li> </ul>

Input / Output	
SAS	<ul style="list-style-type: none"> <li>24 SAS3 ports support via expander and storage Add-on Cards</li> </ul>
LAN	<ul style="list-style-type: none"> <li>2 RJ45 10GBase-T LAN ports</li> <li>1 RJ45 Dedicated IPMI LAN port</li> </ul>
USB	<ul style="list-style-type: none"> <li>3 USB 3.0 ports (2 rear, 1 Type A)</li> </ul>
Video	<ul style="list-style-type: none"> <li>1 VGA Connector</li> </ul>
Serial Header	<ul style="list-style-type: none"> <li>1 Serial header</li> </ul>
DOM	<ul style="list-style-type: none"> <li>2 SuperDOM (Disk on Module) ports</li> </ul>

System BIOS	
BIOS Type	<ul style="list-style-type: none"> <li>AMI 32Mb SPI Flash ROM</li> </ul>

Management	
Software	<ul style="list-style-type: none"> <li>Intel® Node Manager</li> <li><a href="#">Redfish API</a></li> <li><a href="#">IPMI 2.0</a></li> <li>KVM with dedicated LAN</li> <li>NMI</li> <li><a href="#">SSM</a>, <a href="#">SPM</a>, <a href="#">SUM</a></li> <li><a href="#">SuperDoctor@ 5</a></li> </ul>
Power Configurations	<ul style="list-style-type: none"> <li>ACPI Power Management</li> </ul>

PC Health Monitoring	
CPU	<ul style="list-style-type: none"> <li>Monitors for CPU Cores, Chipset Voltages, Memory.</li> <li>4+1 Phase-switching voltage regulator</li> </ul>
FAN	<ul style="list-style-type: none"> <li>Fans with tachometer monitoring</li> <li>Status monitor for speed control</li> <li>Pulse Width Modulated (PWM) fan connectors</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>Monitoring for CPU and chassis environment</li> <li>Thermal Control for fan connectors</li> </ul>

Expansion Slots	
PCI-Express	<ul style="list-style-type: none"> <li>1 PCI-E 3.0 x16 (FH, 10.5" L)</li> <li>5 PCI-E 3.0 x8 (FH, 10.5" L)</li> <li>1 PCI-E 3.0 x8 (LP)</li> <li>1 PCI-E 3.0 x8 (internal LP)</li> </ul> <p>(Both CPUs need to be installed for full access to PCI-E slots and onboard controllers. See manual block diagram and <a href="#">AOC Support</a> for details.)</p>

Drive Bays	
Hot-swap	<ul style="list-style-type: none"> <li>24 Hot-swap 2.5" drive bays: 24 SAS3 via opt. AOC (4 hybrid ports - opt. 4 NVMe)</li> </ul> <p>Note: Storage Add-on card is required</p>

System Cooling	
Fans	<ul style="list-style-type: none"> <li>4 Heavy duty 8cm PWM fans</li> </ul>
Shroud	<ul style="list-style-type: none"> <li>1 Air Shroud</li> </ul>

Power Supply	
1000W Redundant Power Supplies with PMBus	
Total Output Power	<ul style="list-style-type: none"> <li>800W/1000W</li> </ul>
Dimension (W x H x L)	<ul style="list-style-type: none"> <li>73.5 x 40 x 203 mm</li> </ul>
Input	<ul style="list-style-type: none"> <li>100-127Vac / 9.8 - 7A / 50-60Hz</li> <li>200-240Vac / 7 - 5A / 50-60Hz</li> </ul>
+12V	<ul style="list-style-type: none"> <li>Max: 66.7A / Min: 0A (100-127Vac)</li> <li>Max: 83A / Min: 0A (200-240Vac)</li> </ul>
12Vsb	<ul style="list-style-type: none"> <li>Max: 2.1A / Min: 0A</li> </ul>
Output Type	<ul style="list-style-type: none"> <li>25 Pairs Gold Finger Connector</li> </ul>

Certification	  <ul style="list-style-type: none"> <li>UL/cUL/CB/BSMI/CE/CCC Titanium Level</li> <li>[ <a href="#">Test Report</a> ]</li> </ul>
---------------	---

Operating Environment	
RoHS	<ul style="list-style-type: none"> <li>RoHS Compliant</li> </ul>
Environmental Spec.	<ul style="list-style-type: none"> <li>Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F)</li> <li>Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)</li> <li>Operating Relative Humidity: 8% to 90% (non-condensing)</li> <li>Non-operating Relative Humidity: 5% to 95% (non-condensing)</li> </ul>

## Parts List

Parts List - (Items Included)			
	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11DPU	1	Super X11DPU Motherboard
	CSE-219U2E1C4-R1K02-T	1	2U Chassis
			2U Ultra Riser based on Intel X540 controller with 2 10Gbase-T

Add-on Card / Module	AOC-2UR68-I2XT	1	ports, 1 internal PCI-E x8 3.0 slot, 1 PCI-E x16 3.0, and 1 PCI-E x8 3.0 (in x16 slot)
Backplane	BPN-SAS3-216EL1-N4	1	24-port 2U SAS3 12Gbps single-expander backplane, support up to 20x 2.5-inch SAS3/SATA3 HDD/SSD and 4x NVMe/SAS3/SATA3 storage devices
Cable 1	CBL-PWEX-0673	3	8 pin female to 2x big 4 pin female power, 65/70CM, 18AWG,RoHS/REACH
Cable 2	CBL-SAST-0593	2	Internal Mini-SAS HD to Mini-SAS HD 60cm,30AWG,12Gb/s,HF,RoHS/REACH,PBF
Parts	MCP-240-82909-0N	1	Ultra I/O bracket for SC829U, 219U (i2XT),RoHS/REACH
Riser Card	RSC-R1UW-E8R	1	RSC-R1UW-E8R-O-P
Riser Card	RSC-R2UW-4E8	1	RSC-R2UW-4E8-O-P
Heatsink / Retention	SNK-P0068PS	2	2U Passive CPU Heat Sink for X11 Purley Platform Equipped with a Narrow Retention Mechanism
Power Supply	PWS-1K02A-1R	2	1U 1000W Redundant Power Supply 73.5mm width Titanium Level,RoHS/REACH
FAN 1	FAN-0118L4	4	80 x 80 x 38 mm, 9.5K RPM, 4-pin PWM Fan, Hot

### Optional Parts List

	Part Number	Qty	Description
Cable for 4 NVMe Hybrid Drive Bays	2 CBL-SAST-0929 & 2 CBL-SAST-0972	1	OCuLink source to MiniSAS HD target V.91,INT,PCIe NVMe SSD, 57CM,34AWG
2.5" NVMe Drive Tray	MCP-220-00120-0B	4	Tool-less Black gen-3 2.5-inch NVMe drive tray (Orange tab. PUSH button with key lock)
2 Internal M.2 slots (1 SATA, 1 NVMe)	RSC-UMR-8 & CBL-SAST-0538 & MCP-120-82924-0N	1	1U Ultra RHS Riser Card with 1 PCIE/SATA Hybrid M.2 &1 PCIE X8
2 Rear 2.5" Hot-swap SATA Drive Bays	MCP-240-82922-0N-OEM	1	Rear 2x 2.5" HDDs riser bracket kit for SC829U/219U, tool-less
Storage Control Card for SAS3 Drive Bays	AOC-S3008L-L8e	1	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 122HDD, HBA
	AOC-S3008L-L8i		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 63HDD, RAID 0,1,1E
	AOC-S3108L-H8iR		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60
Network Card(s)	AOC-S40G-i2Q	-	Standard LP 2-port 40GbE controller, based on Intel Fortville XL710
	AOC-SGP-i2	-	Standard LP, 2x GbE RJ45, PCI-E x4, Intel i350AM2
	AOC-SGP-i4	-	Standard LP, 4x GbE RJ45, PCI-E x4, Intel i350
	AOC-STG-b4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom BCM57840S
	AOC-STGN-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel 82599ES
	AOC-STGN-i1S	-	Standard LP, 1x 10GbE SFP+, PCI-E x8, Intel 82599EN
	AOC-STG-i2T	-	Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel X540
	AOC-STG-i2	-	Standard LP, 2x 10GbE CX4, PCI-E x8, Intel 82598EB
CachVault(s)	BTR-CV3108-U1	-	CacheVault for Broadcom 3108 with Supercap mounting in 1U 40x56 fan tray
	BTR-TFM8G-LSICVM02 & BKT-BBU-BRACKET-05	-	CacheVault for Broadcom 3108; Supercap mounting bracket for PCI-E location
	BTR-TFM8G-LSICVM02 & MCP-240-00127-0N	-	CacheVault for Broadcom 3108; Supercap mounting bracket for 2.5" HDD location
Global Services & Support	<a href="#">QS4HR3/2/1</a>	-	3/2/1-year onsite 24x7x4 service
	<a href="#">QSNBD3/2/1</a>	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)