

SuperServer 5019P-MT



Views: | [Angled View](#) | [Top View](#) |
| [Front View](#) | [Rear View](#) |

- [▶ Drivers & Utilities](#) | [▶ BIOS](#) | [▶ IPMI](#) | [▶ Tested Memory](#)
- [▶ Tested M.2 List](#) | [▶ Manuals](#) | [▶ OS Certification Matrix](#) | [▶ Quick-References Guide](#) | [▶ Drive Options](#)

Key Features

- **Web Hosting, VM**
- **Application and Data Serving**
- **Database Applications**

1. Single socket P (LGA 3647) supports Intel® Xeon® Scalable Processors
2. Intel® C622 chipset
3. 4 Hot-swap 3.5" SATA3 bays w/ RAID
4. Up to 1TB ECC 3DS LRDIMM, up to DDR4-2666MHz; 8 DIMM slots
5. 1 PCI-E 3.0 x16 slot
6. 2x 10GBase-T ports with Intel X772 + X557
7. Integrated IPMI 2.0 and KVM with Dedicated LAN
8. 1 VGA, 2 COM, 4 USB 3.0, 2 USB 2.0
9. 350W High-efficiency Power Supply Platinum Level Certified

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

Specifications

Product SKUs

SYS-5019P-MT ■ SuperServer 5019P-MT (Black)

Motherboard

Super X11SPi-TF

Processor/Cache

CPU ■ Single Socket P (LGA 3647)
 ■ Intel® Xeon® Scalable Processors
 ■ Support CPU TDP 70-205W

Cores ■ Up to 28 Cores with Intel® HT Technology

System Memory

Memory Capacity ■ 8 DIMM slots
 ■ Up to 1TB ECC 3DS LRDIMM, 256GB ECC RDIMM, DDR4 up to 2666MHz

Memory Type ■ 2666/2400/2133MHz ECC DDR4 SDRAM

On-Board Devices

Chipset ■ Intel® C622 chipset

SATA ■ SATA3 (6Gbps) via C622 controller

Chassis

Form Factor ■ 1U Rackmount

Model ■ CSE-813MFTQC-350CB

Dimensions and Weight

Height ■ 1.7" (43mm)

Width ■ 17.2" (437mm)

Depth ■ 19.8" (503mm)

Package ■ 8.5" (H) x 24" (W) x 29.5" (D)

Weight ■ Gross Weight: 30.4 lbs (13.8 kg)
 ■ Net Weight: 17.6 lbs (8 kg)

Available Colors ■ Black

Front Panel

Buttons ■ Power On/Off button
 ■ System Reset button

LEDs ■ Power LED
 ■ Hard drive activity LED
 ■ Network activity LEDs
 ■ System Overheat LED

Expansion Slots

Network Controllers	<ul style="list-style-type: none"> RAID 0, 1, 5, 10 support Dual 10GBase-T LAN with Intel® X772 + X557
IPMI	<ul style="list-style-type: none"> Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Video	<ul style="list-style-type: none"> ASPEED AST2500 BMC
Input / Output	
SATA	<ul style="list-style-type: none"> 4 SATA3 (6Gbps) ports
LAN	<ul style="list-style-type: none"> 2 RJ45 10GBase-T LAN ports 1 RJ45 Dedicated IPMI LAN port
USB	<ul style="list-style-type: none"> 4 USB 3.0 ports (2 front, 2 rear) 2 USB 2.0 ports (rear)
Video	<ul style="list-style-type: none"> 1 VGA port
Serial Port / Header	<ul style="list-style-type: none"> 2 COM ports (1 rear, 1 header)
SuperDOM	<ul style="list-style-type: none"> 2 SuperDOM (Disk on Module) ports with built-in power
System BIOS	
BIOS Type	<ul style="list-style-type: none"> AMI 32Mb SPI Flash ROM
Management	
Software	<ul style="list-style-type: none"> Intel® Node Manager IPMI 2.0 KVM with dedicated LAN NMI SPM, SUM SuperDoctor® 5 Watch Dog
Power Configurations	<ul style="list-style-type: none"> ACPI Power Management
PC Health Monitoring	
CPU	<ul style="list-style-type: none"> Monitors for CPU Cores, Chipset Voltages, Memory. 4+1 Phase-switching voltage regulator
FAN	<ul style="list-style-type: none"> Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors
Temperature	<ul style="list-style-type: none"> Monitoring for CPU and chassis environment Thermal Control for fan connectors

PCI-Express	<ul style="list-style-type: none"> 1 PCI-E 3.0 x16 slot
Drive Bays / Storage	
Hot-swap	<ul style="list-style-type: none"> 4 Hot-swap 3.5" SATA3 drive bays
M.2	<ul style="list-style-type: none"> M.2 mini-PCI-e support
Peripheral Drives	
Optional	<ul style="list-style-type: none"> Optional slim optical device bay, optional FDD/USB bay
System Cooling	
Fans	<ul style="list-style-type: none"> 4x 40mm mid-fans
Power Supply	
350W AC power supply w/ PFC	
AC Voltage	<ul style="list-style-type: none"> 100-240 V, 50-60 Hz, 4.2-1.8 Amp
+5V	<ul style="list-style-type: none"> Max.: 15 Amp Min.: 0.2 Amp
+5V standby	<ul style="list-style-type: none"> Max.: 3 Amp Min.: 0 Amp
+12V	<ul style="list-style-type: none"> Max.: 29 Amp Min.: 0.5 Amp
-12V	<ul style="list-style-type: none"> Max.: 0.2 Amp Min.: 0 Amp
+3.3V	<ul style="list-style-type: none"> Max.: 12 Amp Min.: 0.2 Amp
Certification	 <ul style="list-style-type: none"> Platinum Level Certified [Test Report]
Operating Environment	
RoHS	<ul style="list-style-type: none"> RoHS Compliant
Environmental Spec.	<ul style="list-style-type: none"> Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)			
	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11Spi-TF	1	Super X11Spi-TF Motherboard
	CSE-813MFTQC-350CB	1	1U Chassis
Backplane	BPN-SAS3-815TQ	1	1U 4-Port 12Gbps Backplane Support 4x3.5" SAS3/SATA3 HDD/SSD
Cable 1	CBL-0186L	1	SATA,INT,ROUND,SET OF 4,ST-RA 56/45.5/35/23CM,26AWG
Cable 2	CBL-CDAT-0661	1	CBL,SGPIO,2X4F TO 2X4F,P2.54,ROUND CABLE,40CM,28AWG
Parts	MCP-120-00031-0N	1	Riser card bracket for SC812,813,813M,815,111,113,113M
Drive Tray(s)	MCP-220-00129-0B	1	Black 2x USB3.0/COM port tray in slim FDD bay
Air Shroud	MCP-310-19007-0N	1	SC811/SC512L/SC512F/SC813M/SC113M/SC513L-410B/SC513L-420B/SC513F, UP X9SRE/I, X9 Mylar Air Shroud, 12"x9.6" MB
Manual	MNL-1920-QRG	1	5019P-MT/MTR, QRG, HF, RoHS/REACH

Riser Card	RSC-RR1U-E16	1	RSC-RR1U-E16 with PIC-E x16 output
Heatsink / Retention	SNK-P0067PS	1	1U Passive CPU Heat Sink for X11 Purley Platform Equipped with a Narrow Retention Mechanism
Power Supply	PWS-350-1H	1	1U Single AC-DC 350W Platinum Level, multiple output power supply (180mm)
FAN 1	FAN-0154L4	4	40x40x28 mm, 22.5K RPM, SC813MF Middle Cooling Fan,RoHS/REACH