

SuperStorage Server 6029P-E1CR12L



Broadcom 3008 AOC



Integrated Board

Super X11DPH-T

- ▶ [Drivers & Utilities](#) ▶ [BIOS](#) ▶ [IPMI](#) ▶ [Tested Memory](#)
- ▶ [Tested M.2 List](#) ▶ [Manuals](#) ▶ [OS Certification Matrix](#) ▶ [Drive Options](#)

Key Features

- Corporate Database
- Database Processing & Storage
- Enterprise Server
- HPC, Data Center
- iSCSI SAN

1. Dual socket P (LGA 3647) supports Intel® Xeon® Scalable Processors, 3 UPI up to 10.4GT/s
2. Up to 2TB ECC 3DS LRDIMM, up to DDR4-2666MHz; 16 DIMM slots
3. 3 PCI-E 3.0 x16, 4 PCI-E 3.0 x8 (slot 2 & 3 occupied by controller and JBOD expansion port)
4. 12 Hot-swap 3.5" SAS3/SATA3 direct attached drive bays
5. Broadcom 3008 SAS3 AOC
6. 2x 10GBase-T LAN ports with Intel X722 + PHY Intel X557
7. Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
8. 3 Hot-swap 8cm redundant PWM fans
9. 1200W Redundant Power Supplies Titanium Level (96%)

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

Specifications

Product SKUs	
SSG-6029P-E1CR12L	▪ SuperServer 6029P-E1CR12L (Black)

Motherboard	
Super X11DPH-T	

Processor/Cache	
CPU	▪ Dual Socket P (LGA 3647) ▪ Intel® Xeon® Scalable Processors, 3 UPI up to 10.4GT/s ▪ Support CPU TDP 70-205W
Cores	▪ Up to 28 Cores with Intel® HT Technology

System Memory	
Memory Capacity	▪ 16 DIMM slots ▪ Up to 2TB ECC 3DS LRDIMM, 512GB

Chassis	
Form Factor	▪ 2U Rackmount
Model	▪ CSE-826BE1C4-R1K23LPB

Dimensions	
Width	▪ 17.2" (437mm)
Height	▪ 3.5" (89mm)
Depth	▪ 24.8" (630mm)
Gross Weight	▪ 61 lbs (27.7 kg)
Available Colors	▪ Black

Front Panel	
Buttons	▪ Power On/Off button ▪ System Reset button
	▪ Power status LED

ECC RDIMM, DDR4 up to 2666MHz

Memory Type	<ul style="list-style-type: none"> 2666/2400/2133MHz ECC DDR4 SDRAM
-------------	--

On-Board Devices

Chipset	<ul style="list-style-type: none"> Intel® C624 chipset
SAS	<ul style="list-style-type: none"> SAS3 (12Gbps) via Broadcom 3008 AOC Broadcom 3008 controller
SATA	<ul style="list-style-type: none"> SATA3 (6Gbps); RAID 0, 1, 5, 10
Network Controllers	<ul style="list-style-type: none"> Dual 10GBase-T LAN ports with Intel X722 + PHY Intel X557
IPMI	<ul style="list-style-type: none"> Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Video	<ul style="list-style-type: none"> ASPEED AST2500 BMC

Input / Output

LAN	<ul style="list-style-type: none"> 2 RJ45 10GBase-T LAN ports 1 RJ45 Dedicated IPMI LAN port
USB	<ul style="list-style-type: none"> 4 USB 3.0 ports (rear) 1 Type A
Video	<ul style="list-style-type: none"> 1 VGA port
Serial Port / Header	<ul style="list-style-type: none"> 1 Fast UART 16550 port / 1 Header

System BIOS

BIOS Type	<ul style="list-style-type: none"> 256Mb AMI UEFI
-----------	--

Management

Software	<ul style="list-style-type: none"> Intel® Node Manager IPMI 2.0 NMI SPM, SUM SuperDoctor® 5 Watchdog
----------	--

PC Health Monitoring

CPU	<ul style="list-style-type: none"> Monitors for CPU Cores, Chipset Voltages, Memory. 4+1 Phase-switching voltage regulator
FAN	<ul style="list-style-type: none"> Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors
Temperature	<ul style="list-style-type: none"> Monitoring for CPU and chassis environment Thermal Control for fan connectors

LEDs	<ul style="list-style-type: none"> Hard drive activity LED Network activity LEDs System Overheat LED Power fail LED
------	---

Expansion Slots

PCI-Express	<ul style="list-style-type: none"> 3 PCI-E 3.0 x16 slot 4 PCI-E 3.0 x8 slots Slot 2 & 3 occupied by controller and JBOD expansion port
-------------	---

Drive Bays

Hot-swap	<ul style="list-style-type: none"> 12 Hot-swap 3.5" SAS3/SATA3 drive bays
Optional	<ul style="list-style-type: none"> 2 Optional Onboard NVMe M.2

Backplane

SAS3 12Gb/s direct attached storage backplane, w/ 24x SAS3 2.5" drive slots


System Cooling

Fans	<ul style="list-style-type: none"> 3 Hot-swap 8cm redundant PWM cooling fans
------	---

Power Supply (76mm Width)

1200W Redundant Power Supplies with PMBus

Total Output Power	<ul style="list-style-type: none"> 1000W/1200W
Dimension (W x H x L)	<ul style="list-style-type: none"> 76 x 40 x 336 mm
Input	<ul style="list-style-type: none"> 100-127Vac / 15-12A / 50-60Hz 200-240Vac / 8.5-7A / 50-60Hz
+12V	<ul style="list-style-type: none"> Max: 83A / Min: 0A (100-127Vac) Max: 100A / Min: 0A (200-240Vac)
+5Vsb	<ul style="list-style-type: none"> Max: 4A / Min: 0A
Output Type	<ul style="list-style-type: none"> 19 Pairs Gold Finger Connector

Certification	 <p>UL/cUL/CB/BSMI/CE/CCC Titanium Level [Test Report]</p>
---------------	---

Operating Environment

RoHS	<ul style="list-style-type: none"> RoHS Compliant
Environmental Spec.	<ul style="list-style-type: none"> Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11DPH-T	1	Super X11DPH-T Motherboard
	CSE-826BE1C4-R1K23LPB	1	2U Chassis
			LSI 3008 based SAS3 HBA, 12Gb, 8 internal ports, 122HDD, Gen3

Add-on Card / Module	AOC-S3008L-L8E	1	x8 Standard Low Profile
Add-on Card / Module	AOM-SAS3-8I8E-LP	1	8-port Mini SAS HD Int-to-Ext cable adapter w/ LP bracket,HF,RoHS/REACH
Backplane	BPN-SAS3-826EL1-N4	1	12-port 2U SAS3 12Gbps single-expander backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD and 4x NVMe/SAS3/SATA3 storage devices
Cable 1	CBL-SAST-0532	4	MINI SAS HD,12G,INT,50CM,30AWG
Parts	MCP-220-82616-0N	1	12G 2.5x2 Drive Kit w/ Status LED(216B/826B/417B/846X/847B)
Parts	MCP-260-00042-0N	1	STD I/O shield for X9 socket R server MB with Gasket.
Heatsink / Retention	SNK-P0068PS	1	2U Passive CPU Heat Sink for X11 Purley Platform Equipped with a Narrow Retention Mechanism
Heatsink / Retention	SNK-P0068PSC	1	2U Passive CPU Heat Sink with a Side Air Channel for X11 Purley Platform Equipped with a Narrow Retention Mechanism
FAN 1	FAN-0158L4	3	80x80x38 mm, 10.5K RPM, Optional Middle Cooling Fan for X10 2U Ultra and HFT Series Servers,RoHS/REACH
Rear Window	MCP-240-82608-0N	1	216B/826B LP rear window,RoHS/REACH,PBF
Power Supply	PWS-1K23A-1R	2	AC-DC 1200W, Titanium Level, Redundancy, 1U, PMBUS 1.2, +12V/+5Vsb, 360x76x40 mm,HF,RoHS/REACH

Optional Parts List

	Part Number	Qty	Description
HDD bracket	MCP-220-82611-0N	1	Dual 2.5" fixed HDD tray
	CBL-0289L	1	HDD Power Cable
	CBL-0473L	2	HDD SATA Cable
Cable	CBL-0099	1	HDD Y-Split Cable
Cable	CBL-SAST-0388L-02	1	Mini-SAS (iPASS) to 4-SATA Cable " To offer 2 SATADOM support on Motherboard
Global Services & Support	QS4HR3/2/1	-	3/2/1-year onsite 24x7x4 service
	QSNBD3/2/1	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)