

FCU792C

Fanless NUC-UTX Embedded Barebone 2 Intel GbE / HDMI+DP / COM / 12V DC-in

Features

- NEW FANLESS CHASSIS ID FOR 2018
- Fanless Embedded Barebone System with Planned Lifecycle Through Q3'2030
- Intel Skylake-U / Kaby Lake-U 15W Processors for High Performance with Low Power
- Supports DDR4-2133 up to 32GB Total Memory
- 2 *Intel Gigabit LAN, HDMI + DisplayPort 4K @60Hz
- 1 * 2.5" SATA Storage Bay
- 1 * mSATA Slot/Mini-PCIE shared slot, 1 * Mini-PCIE Slot (or WIFI installed), 1* Serial (RS232/422/485)
- 6 * USB 3.0 ports, 2 * USB 2.0 ports
- Watchdog Timer, 12V DC-In, 40W AC Adapter
- Includes Wall and Din Rail Mounts



Model	<ul style="list-style-type: none"> ■ FCU792C
Part No	<ul style="list-style-type: none"> ■ HBFCU792CW-7100-B (WIFI), HBFCU792C-7100-B (non-WIFI) ■ HBFCU792CW-xxxx-B (WIFI), HBFCU792C-xxxx-B (non-WIFI) ■ HBFCU792CW-xxxx-T (WIFI, TPM 2.0), HBFCU792C-xxxx-T (non-WIFI, TPM 2.0) ■ CALL FOR OEM CPU OPTIONS
Processor	<ul style="list-style-type: none"> ■ Fanless Intel Core i3-7100U Kaby Lake-U 15W SoC processor
Memory	<ul style="list-style-type: none"> ■ 2 * 260-pin DDR4-2133 SO-DIMM up to 32GB total memory
Storage	<ul style="list-style-type: none"> ■ 1 * 2.5" SATA3 6Gb/s internal bay ■ 1 * Full-size mSATA/Mini-PCIE shared slot
Network	<ul style="list-style-type: none"> ■ 1 * Intel i211-AT gigabit LAN + 1 * Intel i219-LM gigabit LAN ■ WIFI Model: 802.11 b/g/n + BT 4.0 ■ Non-WIFI Model: 1 * Half-size Mini-PCIE slot
Other Features	<ul style="list-style-type: none"> ■ AHCI, Watchdog Timer 10-255 min/sec., AT/ATX Power Mode, Optional Onboard TPM
Front Panel I/O	<ul style="list-style-type: none"> ■ Power button, Power & HDD LED ■ SIM Slot ■ Serial (RS232/422/485) ■ 2 * USB 3.0 ports ■ 2 * USB 2.0 ports
Rear Panel I/O	<ul style="list-style-type: none"> ■ 4 * USB 3.0 ports ■ 2 * RJ45 ■ HDMI 4K @24Hz ■ DisplayPort 4K @60Hz, ■ Line-out/Mic combo jack, Line-in ■ 12V DC-in jack, Antenna holes
BIOS	<ul style="list-style-type: none"> ■ AMI Flash ROM
Box Contents	<ul style="list-style-type: none"> ■ 40W 12V AC Adapter, US Power Cord, Manual, Drivers, Wall/DIN Mount, Antenna (WIFI model)
Compliance	<ul style="list-style-type: none"> ■ CE, FCC, RoHS, ErP Ready
Temperature	<ul style="list-style-type: none"> ■ Operating Temperature 0~50 ° C ■ Storage Temperature -10-70 ° C
Dimensions	<ul style="list-style-type: none"> ■ 144 x 116.9 x 65mm (DxWxH)
Warranty	<ul style="list-style-type: none"> ■ 2 Year limited warranty

*Specifications subject to change without notice, not responsible for typographical errors. Does not include memory, HDD, optical, or OS.



Jetway Computer Corporation
Phone: 510-857-0130 Fax: 510-857-0138
8058 Central Ave., Newark, CA 94560
www.jetwaycomputer.com

