## RMS3200 - 2U Industrial **Rackmount Computer System**

## **Specifications**

#### **Chassis Features**

Material of Chassis 1 2mm SECC Zinc-Coated Steel

**Standard Color** 

Front Door Two Doors with Aluminum Alloy

**Front Panel Connector** 2 x USB 2.0 Ports

Indicators LEDs for Power ON/OFF, HDD, Fan & Alarm

**Speaker** Built-In 0.4W Speaker

**Front Panel Controls** Power ON/OFF, System & Alarm Reset

Cooling Fan 1 x 80mm (Optional: 1 x 60mm)

Air Filter Removeable & Washable

**System Board Size** 12 x 10 Inch (ATX Form Factor Motherboard)

2 x 5.25" External Drive Bays **Drive Bays** 2 x 3.5" External Drive Bays

**Expansion Slots** 3 Slots

2U PS/2 ATX PFC 110/220 VAC Power Supply **Power Supply** 2U Redunant Rackmount ATX Power Supply (Optional)

**Net Weight** 

Dimension (W x H x D) 19 x 3.5 x 18.9 Inch

#### **Environmental**

**Operation Temperature** 50° to 95°F (Regular Motherboard)

32° to 140°F (Industrial Motherboard)

**Non-Operating Temperature** 

**Operating Relative Humidity** 

Non-Operating Relative Humidity

-40° to 158°F

8% to 90% (non-condensing)

5% to 95% (non-condensing)



© 2012 Broadax Systems, Inc. All rights reserved. Specifications subject to change without notice. BSI and the BSI logo are trademarks of Broadax Systems, Inc. Intel, Pentium, Xeon are registered trademarks or trademarks of Intel Corporation. Microsoft, Windows are registered trademarks or trademarks of Microsoft Corporation.

# RMS3200 - 2U Industrial Rackmount Computer System

## Mechanical Drawing

