

17" Industrial Panel PC Comparison Chart



Models	PMS-1178	PMS-1173	PMS-7507	PMS-9172
Front Panel Protection	Industrial-grade plastic	Industrial-grade plastic	Aluminum	Aluminum, IP 65
Display	17" 1280 x 1024 LCD 260cd/m ²	17" 1280 x 1024 LCD 260cd/m ²	17" LCD	17" 1280 x 1024 LCD 260cd/m ²
Touch Screen	Optional 8-wire Resistive	Optional 8-wire Resistive	Optional 7-wire Resistive	Optional 8-wire Resistive
Processor	Intel® Core™2 Duo / Core™ Solo	Intel® Core™2 Duo / Core™ Solo	Intel® Celeron® M ULV 1.0GHz	Intel® Pentium® 4, S478
Memory	DDR2 240-pin DIMM up to 3GB	DDR2 240-pin DIMM up to 3GB	DDR 200-pin SO-DIMM up to 1GB	DDR 333 memory up to 1GB
Slim-type Drive Bay	None	1 x Optical	1 x Optical	1 x FDD, 1 x Optical
HDD Drive Bay	SATA 2 x 3.5" or 2 x 2.5"	SATA 2 x 3.5" or 2 x 2.5"	1 x 2.5" HDD & 1 x IDE CF slot	1 x 2.5" SATA
Expansion Slot	None	2 x PCI slots	1 x PCI slots	2 x PCI slot 1 x Mini PCI
Dimensions	17.71"x 14.56" x 5.9"(W x H x D)	17.48"x 14.25" x 5.12"(W x H x D)	17.32"x 13.54" x 4.21"(W x H x D)	19"x 15.7" x 5.7"(W x H x D)



Models	PMS-5170R	PMS-5270R	PMS-1175
Front Panel Protection	Aluminum, IP 65	Aluminum, IP 65	Aluminum
Display	17" 1280 x 1024 LCD 500:1, 300cd/m ²	17" 1280 x 1024 LCD 500:1, 300cd/m ²	17" 1280 x 1024 LCD 260cd/m ²
Touch Screen	Optional 5-wire Resistive	Optional 5-wire Resistive	Optional Resistive
Processor	Intel® Pentium® 4, S-478 533FSB	Intel® Pentium® 4, S-775 800FSB	Intel® Core 2 Duo/Core Duo/Core Solo
Memory	DDR 333 up to 2GB	DDR 400MHz up to 2GB	DDR2 240-pin DIMM up to 3GB
Slim-type Drive Bay	1 x FDD, 1 x Optical	1 x FDD, 1 x Optical	None
HDD Drive Bay	2 x 2.5" SATA	2 x 3.5" SATA / IDE removable HDD	SATA / IDE 1 x 3.5" or 2 x 2.5"
Expansion Slot	1 x PCI slot, 1 x CF type II socket	1 x PCI slot, 1 x CF type II socket	None
Dimensions	17.79" x 14.01" x 4.33"(W x H x D)	17.79" x 14.01" x 5.59"(W x H x D)	17.5" x 14.25" x 3.25"(W x H x D)