

WSX-732D4 High Performance Tower Workstation

Specifications

Chassis

Standard Color

Front Panel Connector

Indicators

Front Panel Controls

Cooling Fan

System Board Specifications

Drive Bays

Expansion Slots

Power Supply

Net Weight

Dimension (W x H x D)

Operating Temperature

Non-Operating Temperature

Operating Relative Humidity

Non-Operating Relative Humidity

Chassis Features

Mid Tower Chassis

Black

2 x USB 3.0, 2x USB 2.0 ports
2 x Front HD/AC97 Audio ports

Power status LED, Hard drive activity LED, Network activity LED, System Overheat LED

Power On/Off

1 x 120mm Rear Exhaust Fan
1 x 120mm Front Cooling Fan (Optional)
Optimized Cooling Technology at 21dB Whisper-Quiet Operation

Supports Motherboard: X10SAE, X10SAT, X10SRA, X10SRH-CLN4F, X10DAI, X9SRE

3 x 5.25" External Drive Bays
1 x 3.5" External Drive Bays
4 x 3.5" Internal Drive Bays with 90° Rotatable Drive Cage

7 x Expansion Slots

500W 100-240 VAC 80 PLUS Bronze Power Supply w/ PFC
865W 100-240 VAC 80 PLUS Power Supply (Cooling-Redundant) w/ PFC (Optional)
900W 100-240 VAC 80 PLUS Gold Multi Output Power Supply (Optional)

30 lbs (13.6 kg)

7.6" x 16.7" x 20.68" (193 x 424 x 525.3 mm)

Environmental

41°F ~ 95°F

-40°F ~ 140°F

8% ~ 90% (non-condensing)

5% - 95% (non-condensing)

