


SuperServer 2028U-E1CNR4T+ (Complete System Only)



Key Features

• Flexible Connectivity Options

1. Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v3 family; QPI up to 9.6GT/s
2. Up to 1.5TB ECC, up to DDR4 2133MHz; 24x DIMM slots
3. 6x PCI-E 3.0 x8 slots (4x FH, 10.5" L, 1x LP, 1x Internal LP)
4. 4x 10GBase-T ports
5. 24x Hot-swap 2.5" Drive Bays: Default 4x NVMe ports; 24x SAS3 ports via Expander and AOC: AOC-S3108L-H8iR, AOC-S3008L-L8e, AOC-S3008L-L8i
6. 4x heavy duty fans w/ optimal fan speed control; 1x air shroud
7. 1000W High efficiency (96%) Redundant PSU; **Titanium Level**

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

Specifications

Product SKUs

- SYS-2028U-E1CNR4T+** ■ SuperServer 2028U-E1CNR4T+ (**Black**)

Motherboard

Super X10DRU-i+

Processor/Cache

- CPU** ■ Intel® Xeon® processor E5-2600 v3 family (up to 160W TDP) *
 ■ Dual Socket R3 (LGA 2011)

- Cores / Cache** ■ Up to 18 Cores / Up to 45MB Cache

- System Bus** ■ QPI up to 9.6 GT/s

Note * Please contact Supermicro Technical Support for additional information about frequency optimized CPUs and specialized system optimization.

System Memory

- Memory** ■ 24x 288-pin DDR4 DIMM slots

Chassis

- Form Factor** ■ 2U Rackmount

- Model** ■ **CSE-219UE1C4-R1K02**

Dimensions and Weight

- Width** ■ 17.2" (437mm)

- Height** ■ 3.5" (89mm)

- Depth** ■ 27.76" (705.3mm)

- Weight** ■ Net Weight: 36 lbs (16.4 kg)
 ■ Gross Weight: 72 lbs (32.7 kg)

- Available Colors** ■ Black

Front Panel

- Buttons** ■ Power On/Off button
 ■ System Reset button

- LEDs** ■ Power status LED
 ■ HDD activity LED
 ■ 2x Network activity LEDs
 ■ System information (overheat/UID) LED

Expansion Slots

Capacity	<ul style="list-style-type: none"> Up to 1.5TB ECC LRDIMM, RDIMM
Memory Type	<ul style="list-style-type: none"> 2133/1866/1600MHz ECC DDR4 SDRAM 72-bit
DIMM Sizes	<ul style="list-style-type: none"> 64GB, 32GB, 16GB, 8GB, 4GB
Memory Voltage	<ul style="list-style-type: none"> 1.2 V
Error Detection	<ul style="list-style-type: none"> Corrects single-bit errors

On-Board Devices

Chipset	<ul style="list-style-type: none"> Intel® C612 chipset
SATA	<ul style="list-style-type: none"> SATA3 (6Gbps) with RAID 0, 1, 5, 10
IPMI	<ul style="list-style-type: none"> Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support ASPEED AST2400 BMC
Network Connectivity	<ul style="list-style-type: none"> 4x 10GBase-T ports via AOC-2URN4-i4XT Intel® X540 10GBase-T 1x Realtek RTL8211E PHY (dedicated IPMI)
Graphics	<ul style="list-style-type: none"> ASPEED AST2400 BMC

Input / Output

SAS	<ul style="list-style-type: none"> 24x SAS3 ports support via expander and storage Add-on Cards One of the following storage Add-on cards required: <ul style="list-style-type: none"> AOC-S3108-H8iR (12Gbps SAS3/RAID 0, 1, 5, 6, 10, 50, 60, 2GB DDR3 cache, PCI-E Gen3) AOC-S3008L-L8i (12Gbps SAS3/RAID 0,1 and 10, PCI-E Gen3) AOC-S3008L-L8e (12Gbps SAS3/HBA, PCI-E Gen3)
NVMe	<ul style="list-style-type: none"> 4x NVMe ports
LAN	<ul style="list-style-type: none"> 4x RJ45 10GBase-T LAN ports 1x RJ45 Dedicated IPMI LAN port
USB	<ul style="list-style-type: none"> 5x USB 3.0 ports (2 rear, 2 onboard header, 1 Type A)
Video	<ul style="list-style-type: none"> 1x VGA Connector
Serial Port / Header	<ul style="list-style-type: none"> 1x Serial header
DOM	<ul style="list-style-type: none"> 2x SuperDOM (Disk on Module) ports

System BIOS

BIOS Type	<ul style="list-style-type: none"> 128Mb SPI Flash EEPROM with AMI BIOS
BIOS Features	<ul style="list-style-type: none"> Plug and Play (PnP) APM 1.2 PCI 2.3 ACPI 1.0 / 2.0 / 3.0 / 4.0 USB Keyboard support SMBIOS 2.7.1 UEFI 2.3.1

Management

Software	<ul style="list-style-type: none"> SuperDoctor® 5 Intel® Node Manager 3.0 Watch Dog NMI SMCBU and SMM
-----------------	--

PCI-Express

- Up to 6x PCI-E 3.0 x8 slots (4x FH, 10.5" L, 1x LP, 1x Internal LP)

(Both CPUs need to be installed for full access to PCI-E slots and onboard controllers. See manual block diagram and [AOC Support](#) for details.)

Drive Bays

Hot-swap	<ul style="list-style-type: none"> 24x 2.5" Hot-swap drive bays Default 4x NVMe ports 24x SAS3 ports support via Expander and AOC
-----------------	--

Note: Storage Add-on card is required

System Cooling

Fans	<ul style="list-style-type: none"> 4x 8cm heavy duty PWM fans
Shroud	<ul style="list-style-type: none"> 1x Air Shroud

Power Supply with Digital Switching Control

1000W Redundant Titanium Level (96%) Single Output Power Supplies

AC Input	<ul style="list-style-type: none"> 100-127 V, 50-60 Hz 200-240 V, 50-60 Hz
+12V	<ul style="list-style-type: none"> Max: 62.5A & Min: 0A (100Vac-127Vac) Max: 83A (200Vac-240Vac) & Min: 0A
12V SB	<ul style="list-style-type: none"> Max: 2.1A Min: 0A

Certification	  Titanium Level [Test Report]
----------------------	---

PC Health Monitoring

Voltage	<ul style="list-style-type: none"> Monitors for CPU Cores, +1.8V, +3.3V, +5V, +12V, +3.3V Standby, +5V Standby, VBAT, Memory Voltages. 5+1 Phase-switching voltage regulator
FAN	<ul style="list-style-type: none"> 8x 4-pin fan headers Status monitor for speed control Pulse Width Modulated (PWM) fan connectors
Temperature	<ul style="list-style-type: none"> Support to monitor Supermicro AOC temperatures from IPMI or SD 5 Monitoring for CPU and chassis environment CPU thermal trip support Thermal Control for 8x Fan Connectors Thermal Monitor 2 (TM2) support PECI
LED	<ul style="list-style-type: none"> Memory DIMM ECC error LEDs CPU / System Overheat LED Suspend static indicator LED UID/Remote UID
Other Features	<ul style="list-style-type: none"> 4x 8-pin GPU power connectors Chassis intrusion detection Chassis intrusion header SDDC Support RoHS

Operating Environment / Compliance

RoHS	<ul style="list-style-type: none"> RoHS Compliant
	<ul style="list-style-type: none"> Operating Temperature: 10°C to 35°C (50°F to 95°F)

Power Configurations

- Optional IPMI 1.5 / 2.0
- ACPI Power Management
- Power-on mode for AC power recovery

Environmental Spec.

- Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)
- Operating Relative Humidity: 8% to 90% (non-condensing)
- Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X10DRU-i+	1	Super X10DRU-i+ Motherboard
	CSE-219UE1C4-R1K02	1	2U Chassis
Add-on Card / Module	AOC-2URN4-I4XT	1	2U Ultra Riser based on Intel X540 controller with 4 10Gbase-T ports, 4 NVMe ports, and 1 internal PCI-E x8 3.0 slot
Air Shroud	MCP-310-82912-0N	1	
Backplane	BPN-SAS3-216EL1-N4	1	24 port SAS3 12G expander backplane, support up to 20x2.5
Cable 1	CBL-SAST-0593	2	Internal Mini-SAS HD to Mini-SAS HD 60cm,30AWG,12Gb/s,HF,RoHS/REACH,PBF
Cable 2	CBL-PWEX-0673	3	8 pin female to 2x big 4 pin female power, 65/70CM, 18AWG,RoHS/REACH
Cable 3	CBL-SAST-0658	4	Internal Mini-SAS HD cable for PCIe SSD NVMe, 12Gb/s, 60cm,30AWG,RoHS/REACH
Drive Tray(s)	MCP-220-00127-0B	4	Black gen-3 2.5 NVMe drive tray, Orange tab with lock (for hotswap NVMe drive),HF,RoHS/REACH
Label	LBL-0108	1	CAUTION LABEL FOR REDUNDANT PWR SYSTEMS
Manual	MNL-1750-QRG	1	SYS-2028U-E1CNR(4)T+, QRG,HF,RoHS/REACH
Riser Card	RSC-R1UW-E8R	1	RSC-R1UW-E8R-O-P
Riser Card	RSC-R2UW-4E8	1	RSC-R2UW-4E8-O-P
Heatsink / Retention	SNK-P0058PSU	2	2U Passive CPU Heat Sink for X10 2U 24-DIMM Ultra Series Servers,RoHS/REACH
Power Supply	PWS-1K02A-1R	2	1U 1000W Redundant Power Supply 73.5mm width Titanium Level,RoHS/REACH
Mounting Rails	MCP-290-00053-0N	1	Inner/outer rail set, quick-release type, 26.5" to 36.4"
	MCP-290-00060-0N	1	Threaded rail adapter default for round hole rack

Optional Parts List

	Part Number	Qty	Description
Mounting Rails	MCP-290-00053-0N	-	Inner/outer rail set, quick-release type, 26.5" to 36.4"
	MCP-290-00060-0N	-	Threaded rail adapter default for round hole rack
Storage Control Card and Cable(s)	AOC-S3008L-L8e	-	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 122HDD, HBA
	AOC-S3008L-L8i	-	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 63HDD, RAID 0,1,1E
	AOC-S3108L-H8iR	-	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60
Network Card(s)	AOC-S40G-i2Q	-	Standard LP 2-port 40GbE controller, based on Intel Fortville XL710
	AOC-SGP-i2	-	Standard LP, 2x GbE RJ45, PCI-E x4, Intel i350AM2
	AOC-SGP-i4	-	Standard LP, 4x GbE RJ45, PCI-E x4, Intel i350
	AOC-STG-b4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom BCM57840S
	AOC-STGN-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel 82599ES
	AOC-STGN-i1S	-	Standard LP, 1x 10GbE SFP+, PCI-E x8, Intel 82599EN
	AOC-STG-i2T	-	Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel X540
	AOC-STG-i2	-	Standard LP, 2x 10GbE CX4, PCI-E x8, Intel 82598EB
CachVault(s)	BTR-CV3108-U1	-	CacheVault for LSI 3108 with Supercap mounting for 2U Ultra
	BTR-TFM8G-LSICVM02 & BKT-BBU-BRACKET-05	-	CacheVault for LSI 3108; Supercap mounting bracket for PCI-E location
	BTR-TFM8G-LSICVM02 & MCP-240-00127-0N	-	CacheVault for LSI 3108; Supercap mounting bracket for 2.5" HDD location
Onsite Service Program	QS4HR3/2/1	-	3/2/1-year onsite 24x7x4 service
Onsite Service Program	OSNBD3/2/1	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)