

RMK-DU17 2U LCD Keyboard Drawer Specifications

PRODUCT	RMK-DU17
DISPLAY	DUAL 17.3" FULL HD 1920 X 1080, 16:9 DISPLAY
VIEWING ANGLE	DISPLAYS TILT ~15° FROM VERTICAL
PORTS	2X USB 2.0 INPUTS ON FRONT + 2X USB 2.0 INPUTS ON REAR ANALOG VGA, DVI-D, DISPLAY PORT
POWER SUPPLY	115/230 VAC, 50/60HZ, 100W MAX
KEYBOARD & MOUSE	101 KEYS BACKLIT KEYBOARD WITH TOUCHPAD AND ADJUSTABLE BRIGHTNESS. RESISTIVE TOUCHPAD OPTIONAL: WATERPROOF KEYBOARD
DIMENSIONS	HEIGHT: 2U - 3.46" (88MM) WIDTH: 17.76" (451MM) DEPTH: 25.89" (657.6MM) RACK DEPTH: 24" (609.6MM)
WEIGHT	~42 LBS (19KG)
TEMPERATURE	MIL-STD-810E (501.4, 502.4), OPERATING: 0 ~ 50°C, NON-OPERATING: -40 ~ 70°C
HUMIDITY	MIL-STD-810E (507.2), RELATIVE HUMIDITY: 5% TO 95% OPERATING, NON-CONDENSING
ALTITUDE	MIL-STD-810E (500.3), OPERATING: 15,000 FT (4571.8 M), NON-OPERATING: 40,000 FT (12,192 M)
VIBRATION	MIL-STD-810E (514.4) OPERATING: 10 TO 500 HZ 1.04 G (RMS)
SHOCK	MIL-STD-810E (516.4), OPERATING: 15 G, 8 MS 1/2 SINE, NON-OPERATING: 40 G, 8 MS 1/2 SINE
DROP	4" STAND ALONE, 39" TRANSIT DROP IN TRANSIT CASE

* The technical specifications are an example of the system's capabilities. They can be customized specifically for your needs. If you have any questions, feel free to contact one of our sales representatives.