

# RMK-DU19 2U LCD Keyboard Drawer Specifications

<b>PRODUCT</b>	RMK-DU19
<b>DISPLAY</b>	DUAL 19" SXGA 1280 X 1024
<b>VIEWING ANGLE</b>	DISPLAYS TILT ~15° FROM VERTICAL
<b>PORTS</b>	INTERNAL USB 2.0 HUB + 2X USB 2.0 INPUTS ON FRONT + 1X USB 2.0 INPUTS ON REAR, ANALOG VGA, DVI-D, DISPLAYPORT FOR EACH DISPLAY
<b>POWER SUPPLY</b>	115/230 VAC, 50/60HZ, 100W MAX
<b>KEYBOARD &amp; MOUSE</b>	101 KEYS BACKLIT KEYBOARD WITH TOUCHPAD AND ADJUSTABLE BRIGHTNESS. RESISTIVE TOUCHPAD OPTIONAL: WATERPROOF KEYBOARD
<b>DIMENSIONS</b>	HEIGHT: 2U - 3.46" (88MM) WIDTH: 17.76" (451MM) DEPTH: 25.89" (657.6MM)
<b>WEIGHT</b>	~45 LBS (20.5KG)
<b>TEMPERATURE</b>	MIL-STD-810E (501.4, 502.4), OPERATING: 0 ~ 50°C, NON-OPERATING: -40 ~ 70°C
<b>HUMIDITY</b>	MIL-STD-810E (507.2), RELATIVE HUMIDITY: 5% TO 95% OPERATING, NON-CONDENSING
<b>ALTITUDE</b>	MIL-STD-810E (500.3), OPERATING: 15,000 FT (4571.8 M), NON-OPERATING: 40,000 FT (12,192 M)
<b>VIBRATION</b>	MIL-STD-810E (514.4), OPERATING: 10 TO 500 HZ 1.04 G (RMS)
<b>SHOCK</b>	MIL-STD-810E (516.4), OPERATING: 15 G, 8 MS 1/2 SINE, NON-OPERATING: 40 G, 8 MS 1/2 SINE
<b>DROP</b>	4" STAND ALONE, 39" TRANSIT DROP IN TRANSIT CASE

\* The technical specifications are an example of the system's capabilities. They can be customized specifically for your needs. If you have any questions, feel free to contact one of our sales representatives.