


# SuperServer 6018R-WTR



## Integrated Board



**Super X10DRW-i**



## Key Features

1. Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v3 family; QPI up to 9.6GT/s
2. Up to 1TB ECC DDR4 2133MHz; 16x DIMM sockets
3. 2x PCI-E 3.0 x16 (FHHL) - AOC support
4. Intel® i350 Dual port GbE LAN
5. 4x 3.5" Hot-swap SAS/SATA HDD Bays for Customizable Storage SAS 3.0 (12Gbps) support
6. I/O ports: 2x SuperDOM, 1x VGA, 1x Serial, 6x USB 3.0 (4 rear)
7. 700W Redundant Power Supplies Platinum Level High-efficiency

Available Colors:

Black



Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

## Specifications

### Product SKUs

SYS-6018R-WTR	■ SuperServer 6018R-WTR (Black)
---------------	---------------------------------

### Motherboard

Super X10DRW-i

### Processor/Cache

CPU	■ Intel® Xeon® processor E5-2600 v3 family (up to 145W TDP **) ■ Dual Socket R3 (LGA 2011)
-----	---

Cores / Cache	■ Up to 18 Cores / Up to 45MB Cache
---------------	-------------------------------------

System Bus	■ QPI up to 9.6 GT/s
------------	----------------------

Note	** Please contact your Supermicro sales representative for additional details.
------	--

### System Memory

Memory Capacity	■ 16x 288-pin DDR4 DIMM sockets ■ Up to 1TB ECC LRDIMM, 512GB ECC RDIMM
Memory Type	■ 2133/1866/1600MHz ECC DDR4 SDRAM 72-bit

### Chassis

Form Factor	■ 1U Rackmount
Model	■ CSE-815TQ-R706WB

### Dimensions and Weight

Width	■ 17.2" (437mm)
Height	■ 1.7" (43mm)
Depth	■ 25.6" (650mm)
Gross Weight	■ 36 lbs (18.1kg)
Available Colors	■ Black

### Front Panel

Buttons	■ Power On/Off button ■ System Reset button ■ UID button
LEDs	■ Power status LED ■ HDD activity LED ■ 2x Network activity LEDs ■ Universal Information (UID) LED

### Expansion Slots

	■ 2 PCI-E 3.0 x16 full-height, Half-length slots
--	--

DIMM Sizes	<ul style="list-style-type: none"> <li>RDIMM: 32GB, 16GB, 8GB, 4GB</li> <li>LRDIMM: 64GB, 32GB</li> </ul>
Memory Voltage	<ul style="list-style-type: none"> <li>1.2 V</li> </ul>
Error Detection	<ul style="list-style-type: none"> <li>Corrects single-bit errors</li> </ul>
<b>On-Board Devices</b>	
Chipset	<ul style="list-style-type: none"> <li>Intel® C612 Express chipset</li> </ul>
SATA	<ul style="list-style-type: none"> <li>SATA3 via Intel® C612; RAID 0, 1, 5, 10</li> </ul>
IPMI	<ul style="list-style-type: none"> <li>Support for Intelligent Platform Management Interface v.2.0</li> <li>IPMI 2.0 with virtual media over LAN and KVM-over-LAN support</li> <li>ASPEED AST2400 BMC</li> </ul>
Network Controllers	<ul style="list-style-type: none"> <li>Intel® i350 Dual Port Gigabit Ethernet Controller</li> <li>Virtual Machine Device Queues reduce I/O overhead</li> <li>Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output</li> <li>1x Realtek RTL8211E PHY (dedicated IPMI)</li> </ul>
Graphics	<ul style="list-style-type: none"> <li>ASPEED AST2400 BMC</li> </ul>
<b>Input / Output</b>	
SATA/SAS	<ul style="list-style-type: none"> <li>10x SATA3 (6Gbps) ports</li> </ul>
LAN	<ul style="list-style-type: none"> <li>2x RJ45 Gigabit Ethernet LAN ports</li> <li>1x RJ45 Dedicated IPMI LAN port</li> </ul>
USB	<ul style="list-style-type: none"> <li>6x USB 3.0 ports (4 rear + 2 via header)</li> </ul>
Video	<ul style="list-style-type: none"> <li>1x VGA port</li> </ul>
Serial Port / Header	<ul style="list-style-type: none"> <li>1x Header</li> </ul>
DOM	<ul style="list-style-type: none"> <li>2x SuperDOM (Disk on Module) ports</li> </ul>
<b>Management</b>	
Software	<ul style="list-style-type: none"> <li>SuperDoctor® 5</li> <li>Watch Dog</li> <li>NMI</li> <li>IPMI 2.0</li> <li>Intel Node Manager</li> </ul>
Power Configurations	<ul style="list-style-type: none"> <li>ACPI / APM Power Management</li> <li>Power-on mode for AC power recovery</li> </ul>

PCI-Express	<ul style="list-style-type: none"> <li>1x PCI-E 3.0 x8 Mezzanine for HBA cards</li> <li><a href="#">UIO AOC Compatibility Matrix</a></li> </ul> <p>(Both CPUs need to be installed for full access to PCI-E slots and onboard controllers. See manual block diagram and <a href="#">AOC Support</a> for details.)</p>
<b>Drive Bays</b>	
Hot-swap	<ul style="list-style-type: none"> <li>4x 3.5" Hot-swap SAS / SATA HDD trays (ready for PCI-E storage controller card)</li> </ul>
<b>Peripheral Drives</b>	
DVD-ROM	<ul style="list-style-type: none"> <li>Slim DVD-ROM drive (optional)</li> </ul>
<b>Backplane</b>	
SAS/SATA HDD Backplane (SAS support requires optional SAS controller)	
<b>System Cooling</b>	
Fans	<ul style="list-style-type: none"> <li>5x 4cm Counter-rotating PWM fans</li> </ul>
<b>Power Supply</b>	
700W/750W Redundant AC-DC high-efficiency power supply with PMBus and I2C	
AC Voltage	<ul style="list-style-type: none"> <li>700W: 100 - 140 V, 50-60 Hz</li> <li>750W: 200 - 240V, 50-60 Hz</li> </ul>
DC Output +5V standby	<ul style="list-style-type: none"> <li>3 Amp</li> </ul>
DC Output +12V	<ul style="list-style-type: none"> <li>700W: 58 Amp @ 100-140V</li> <li>750W: 62 Amp @ 200-240V</li> </ul>
Certification	 <ul style="list-style-type: none"> <li>Platinum Certified (Cert. in progress)</li> </ul>
<b>System BIOS</b>	
BIOS Type	<ul style="list-style-type: none"> <li>128Mb SPI Flash EEPROM with AMI BIOS</li> </ul>
BIOS Features	<ul style="list-style-type: none"> <li>Plug and Play (PnP)</li> <li>APM 1.2</li> <li>PCI 2.2</li> <li>ACPI 1.0 / 2.0 / 3.0 / 4.0</li> <li>BIOS resuce hot keys</li> <li>USB Keyboard support</li> <li>SMBIOS 2.3</li> <li>UEFI</li> </ul>
<b>Operating Environment / Compliance</b>	
RoHS	<ul style="list-style-type: none"> <li>RoHS Compliant</li> </ul>
Environmental Spec.	<ul style="list-style-type: none"> <li>Operating Temperature: 10°C to 35°C (50°F to 95°F)</li> <li>Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)</li> <li>Operating Relative Humidity: 8% to 90% (non-condensing)</li> <li>Non-operating Relative Humidity: 5% to 95% (non-condensing)</li> </ul>

## Parts List

Parts List - (Items Included)			
	Part Number	Qty	Description
Motherboard / Chassis	MBD-X10DRW-i	1	Super X10DRW-i Motherboard
	CSE-815TQ-R706WB	1	1U Chassis
Backplane	BPN-SAS-815TQ-O-P	1	BPN-SAS-815TQ-O-P
Cable 1	CBL-0186L	1	SET OF 4 SATA 56/45.5/35/23CM ROUND S-RA. 26AWG
Cable 2	CBL-CDAT-0661	1	8 pin to 8 pin round SGPIO cable, 40cm, 28AWG, pinout 1-1,RoHS/REACH
Riser Card	RSC-R1UW-2E16-O-P	1	RSC-R1UW-2E16-O-P
Heatsink / Retention	SNK-P0047PSC	1	1U Passive Front CPU Heat Sink w/ a Side Air Channel for X9, X10 Systems Equipped with a Narrow ILM MB
Heatsink / Retention	SNK-P0057PS	1	1U High Performance Passive CPU Heat Sink for X9, X10 Systems Equipped w/ a Narrow ILM MB
Power Supply	PWS-706P-1R	2	1U 750W redundant power width 54.5mm(Platinum),HF,RoHS/REACH,PBF
Rail Set	CSE-PT51L	1 set	Silver chassis rail set for SC813,814,815,816,819
Optional Parts List			
	Part Number	Qty	Description
DVD-ROM / DVD-RW	DVM-PNSC-DVD-SBT1 DVM-TEAC-DVD-SBT2 DVM-PLDS-DVDRW-SBT2 DVM-TEAC-DVDRW-SBT1	1	SLIM DVD-ROM / DVD-RW SATA DRIVE
DVD-ROM Accessory	MCP-220-81502-0N	1	Slim SATA DVD kit
Internal 2.5" HDD Tray (FDD Slot)	MCP-220-83601-0B	1	Black FDD dummy tray support 1x 2.5" slim HDD
Internal 2.5" HDD Tray (DVD Slot)	MCP-290-00036-0B	1	Black DVD dummy tray support 1x 2.5" HDD
USB/COM Port Tray (FDD Slot)	CSE-PT40L-B0	1	Black USB/COM port tray in slim FDD bay
Rail Set	MCP-290-00054-0N	1 set	Rail set, quick/quick, optional for 1U 17.2"W SC815
Network Card(s)	AOC-SGP-i2	-	Standard LP, 2x GbE RJ45, PCI-E x4, Intel@i350AM2
	AOC-SGP-i4	-	Standard LP, 4x GbE RJ45, PCI-E x4, Intel@i350
	AOC-SG-i2	-	Standard LP, 2x GbE RJ45, PCI-E x4, Intel@82575EB
	AOC-SG-i4	-	Standard LP, 4x GbE RJ45, PCI-E x4, Intel@82576EB
	AOC-STG-b4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom@BCM57840S
	AOC-STGN-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel@82599ES
	AOC-STG-i2T	-	Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel@X540
	AOC-STG-i2	-	Standard LP, 2x 10GbE CX4, PCI-E x8, Intel@82598EB
Storage Controller Card(s)	AOC-S3008L-L8e	-	Standard LP, 8 internal ports (12Gb/s) Gen-3, 122HDD, HBA
	AOC-S3008L-L8i	-	Standard LP, 8 internal ports (12Gb/s) Gen-3, 63HDD, RAID 0,1,1E
	AOC-S3108L-H8iR	-	Standard LP, 8 internal ports (12Gb/s) Gen-3, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60
	AOC-S2308L-L8e	-	Standard LP, 8 internal ports (6Gb/s) Gen-3, 122HDD, HBA
	AOC-S2308L-L8i	-	Standard LP, 8 internal ports (6Gb/s) Gen-3, 63HDD, RAID 0,1,1E
	AOC-S2208L-H8iR	-	Standard LP, 8 internal ports (6Gb/s) Gen-3, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60
	AOC-SAS2LP-MV8	-	Standard LP, 8 internal ports (6Gb/s) Gen-2, HBA
	AOC-SAS2LP-H4iR	-	Standard LP, 4 internal & 4 external ports (6Gb/s) Gen-2, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60
	AOC-SAS2LP-H8iR	-	Standard LP, 8 internal ports (6Gb/s) Gen-2, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60