

SuperServer 1028U-TRT+ (Complete System Only)



Integrated Board



X10DRU-i+



Key Features

1. Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v3 family; QPI up to 9.6GT/s
2. Up to 1.5TB ECC, up to DDR4 2133MHz; 24x DIMM sockets
3. 2x PCI-E 3.0 x16 slots (FH, 10.5" L), 2x PCI-E 3.0 x8 slots (LP, 1 internal)
4. 2x 10GBase-T ports
5. 10x Hot-swap 2.5" Drive Bays: 10x SATA3 ports by default; optional 8x SAS3 ports
6. 4x heavy duty fans w/ optimal fan speed control
7. 750W Redundant Power Supplies **Platinum Level (94%+)**

Due to the complexity of integration, this product is sold as completely assembled systems only (including but not limited to CPUs, memory, and HDDs). Please contact your Supermicro sales rep for special requirements.

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

Specifications

Product SKUs

- SYS-1028U-TRT+**
- SuperServer 1028U-TRT+ (Black)

Motherboard

Super X10DRU-i+

Processor/Cache

- CPU**
- Intel® Xeon® processor E5-2600 v3 family (up to 160W TDP **)
 - Dual Socket R3 (LGA 2011)

- Cores / Cache**
- Up to 18 Cores / Up to 45MB Cache

- System Bus**
- QPI up to 9.6 GT/s

- Note**
- ** Please contact your Supermicro sales representative for additional details.

System Memory

- Memory Capacity**
- 24x 288-pin DDR4 DIMM slots
 - Up to 1.5TB ECC LRDIMM, 768GB ECC RDIMM

- Memory Type**
- 133/1866/1600MHz ECC DDR4 SDRAM 72-bit

Chassis

- Form Factor**
- 1U Rackmount

- Model**
- CSE-119UAC-R750

Dimensions and Weight

- Height**
- 1.7" (43mm)

- Width**
- 17.2" (437mm)

- Depth**
- 27.8" (707mm)

- Gross Weight**
- 48 lbs (21.8 kg)

- Available Color**
- Black

Front Panel

- Buttons**
- Power On/Off button
 - System Reset button

- LEDs**
- Power LED
 - Hard drive activity LED
 - 2x Network activity LEDs
 - System Overheat LED / Fan fail LED / UID LED

Expansion Slots

DIMM Sizes	<ul style="list-style-type: none"> RDIMM: 32GB, 16GB, 8GB, 4GB LRDIMM: 64GB, 32GB
Memory Voltage	<ul style="list-style-type: none"> 1.2 V
Error Detection	<ul style="list-style-type: none"> Corrects single-bit errors

On-Board Devices

Chipset	<ul style="list-style-type: none"> Intel® C612 Express chipset
SATA	<ul style="list-style-type: none"> SATA3 (6Gbps) with RAID 0, 1, 5, 10
IPMI	<ul style="list-style-type: none"> Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support ASPEED AST2400 BMC
Network Connectivity	<ul style="list-style-type: none"> 2x 10GBase-T ports via AOC-UR-i2XT
Graphics	<ul style="list-style-type: none"> ASPEED AST2400 BMC

Input / Output

SATA	<ul style="list-style-type: none"> 10x SATA3 (6Gbps) ports
SAS	<ul style="list-style-type: none"> 8x SAS3 ports support via optional Add-on Card
LAN	<ul style="list-style-type: none"> 2x RJ45 10GBase-T ports 1x RJ45 Dedicated IPMI LAN port
USB	<ul style="list-style-type: none"> 5x USB 3.0 ports (2 rear, 2 onboard header, 1 Type A)
Video	<ul style="list-style-type: none"> 1x VGA Connector
Serial Port	<ul style="list-style-type: none"> 1x Serial header

System BIOS

BIOS Type	<ul style="list-style-type: none"> 128Mb SPI Flash EEPROM with AMI BIOS
BIOS Features	<ul style="list-style-type: none"> Plug and Play (PnP) APM 1.2 PCI 2.3 ACPI 1.0 / 2.0 / 3.0 / 4.0 USB Keyboard support SMBIOS 2.7.1 UEFI 2.3.1

Management

Software	<ul style="list-style-type: none"> SuperDoctor® 5 Intel® Node Manager 3.0 Watch Dog NMI SMCBU and SMM Optional IPMI 1.5 / 2.0
Power Configurations	<ul style="list-style-type: none"> ACPI Power Management Power-on mode for AC power recovery

- 2x PCI-E 3.0 x16 slots (Full-height, 10.5" L)
- 2x PCI-E 3.0 x8 slots (Low-profile, 1 internal)

PCI-Express

(Both CPUs need to be installed for full access to PCI-E slots and onboard controllers. See manual block diagram and [AOC Support](#) for details.)

Drive Bays

Hot-swap	<ul style="list-style-type: none"> 10x 2.5" Hot-swap drive bays
-----------------	--

System Cooling

Fans	<ul style="list-style-type: none"> 4x heavy duty fans with optimal fan speed control 4x additional fans optional
Air Shroud	<ul style="list-style-type: none"> 1x Air Shroud

Power Supply

750W Redundant AC-DC Power Supplies, +12V/+12Vsb output

AC Input	<ul style="list-style-type: none"> 100-127Vac, 50-60Hz 200-240Vac, 50-60Hz
+12V	<ul style="list-style-type: none"> Max: 62.5A & Min: 0A (100Vac-127Vac) Max: 62.5A & Min: 0A (200Vac-240Vac)
12V SB	<ul style="list-style-type: none"> Max: 2.1A Min: 0A

Certification



Platinum Level

[Test Report]

PC Health Monitoring

Voltage	<ul style="list-style-type: none"> Monitors for CPU Cores, +1.8V, +3.3V, +5V, +12V, +3.3V Standby, +5V Standby, VBAT, Memory Voltages. 5+1 Phase-switching voltage regulator
FAN	<ul style="list-style-type: none"> 8x 4-pin fan headers Status monitor for speed control Pulse Width Modulated (PWM) fan connectors
Temperature	<ul style="list-style-type: none"> Support to monitor Supermicro AOC temperatures from IPMI or SD 5 Monitoring for CPU and chassis environment CPU thermal trip support Thermal Control for 8x Fan Connectors Thermal Monitor 2 (TM2) support PECI
LED	<ul style="list-style-type: none"> Memory DIMM ECC error LEDs CPU / System Overheat LED Suspend static indicator LED UID/Remote UID
Other Features	<ul style="list-style-type: none"> 4x 8-pin GPU power connectors Chassis intrusion detection Chassis intrusion header SDDC Support RoHS

Operating Environment / Compliance

RoHS	<ul style="list-style-type: none"> RoHS Compliant
Environmental Spec.	<ul style="list-style-type: none"> Operating Temperature: 5°C to 40°C (41°F to 104°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing)

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X10DRU-i+	1	Super X10DRU-i+ Motherboard
	CSE-119UAC-R750	1	CSE-119UAC-R750 Chassis
Air Shroud	MCP-310-11803-0N	1	Air Shroud for Air X9DRG/X10DRG boards in CSE-118GH-R1K66B
Backplane	BPN-SAS3-116A	1	1U SAS3 12Gbps 10x 2.5" HDD backplane for 1U Storage Chassis,RoHS/REACH,PBF
Cable 1	CBL-0484L	2	55cm 30AWG SATA S-S cable
Cable 2	CBL-CDAT-0662	1	8 pin to 8 pin round SGPIO cable, 61.5cm, 28AWG, pinout 1-1,RoHS/REACH
Cable 3	CBL-PWEX-0650	1	8 pin female to 2x RA(Right Angle) big 4 pin female power, 47/62CM, 18AWG,RoHS/REACH
Cable 4	CBL-SAST-0655	1	Internal RA side exit (right) miniSAS to miniSAS HD 47cm w/ SB, 30AWG,RoHS/REACH
Cable 5	CBL-SAST-0656	1	Internal RA side exit (right) miniSAS to miniSAS HD 39cm w/ SB, 30AWG,RoHS/REACH
Riser Card	RSC-R1UW-E8R	1	RSC-R1UW-E8R-O-P
Riser Card	RSC-R1UW-2E16	1	RSC-R1UW-2E16-O-P
Heatsink / Retention	SNK-P0047PS	2	1U Passive CPU Heat Sink for X9, X10 Systems Equipped w/ a Narrow ILM MB
Power Supply	PWS-750P-1R	2	1U 750W CRPS, +12V/+12Vsb output, 80-plus Platinum AC-DC Power Supply Module (185x74x40mm),RoHS/REACH,PBF
Cable 6	CBL-0160L	2	NEMA5-15P to C13 US power cord 16AWG 6ft, PBF (default for high watt)
Cable 7	CBL-0335L	1	FRONT CTL CABLE 20 PIN TO 20 PIN W/TUBE,73CM,PBF. 28AWG
Drive Tray(s)	MCP-220-00047-0B	10	Black gen 3rd hot-swap 2.5inch HDD tray
Fan 1	FAN-0101L4	4	40x56,4 Pin PWM,Primary for SC809,111, Sec.for SC816,819,808
Add-on Card	AOC-UR-i2XT	1	AOC for 2x 10GBase-T ports

Optional Parts List

	Part Number	Qty	Description
Storage Control Card and Cable(s)	AOC-S3008L-L8e & 1x CBL-SAST-0671	-	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 122HDD, HBA; Internal RA side exit (left) dual miniSAS HD to 2x miniSAS HD 50cm,30AWG,12Gb/s
	AOC-S3008L-L8i & 1x CBL-SAST-0671	-	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 63HDD, RAID 0,1,1E; Internal RA side exit (left) dual miniSAS HD to 2x miniSAS HD 50cm,30AWG,12Gb/s
	AOC-S3108L-H8iR & 1x CBL-SAST-0671	-	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60; Internal RA side exit (left) dual miniSAS HD to 2x miniSAS HD 50cm,30AWG,12Gb/s
Network Card(s)	AOC-S40G-i2Q	-	Standard LP 2-port 40GbE controller, based on Intel Fortville XL710
	AOC-SGP-i2	-	Standard LP, 2x GbE RJ45, PCI-E x4, Intel® i350AM2
	AOC-SGP-i4	-	Standard LP, 4x GbE RJ45, PCI-E x4, Intel® i350
	AOC-STG-b4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom® BCM57840S
	AOC-STGN-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel® 82599ES
	AOC-STGN-i1S	-	Standard LP, 1x 10GbE SFP+, PCI-E x8, Intel® 82599EN
	AOC-STG-i2T	-	Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel® X540
	AOC-STG-i2	-	Standard LP, 2x 10GbE CX4, PCI-E x8, Intel® 82598EB
CachVault(s)	BTR-TFM8G-LSICVM02	-	CacheVault for LSI 3108 (LSICVM02)
	BTR-CV3108-1U1	-	LSI 3108 CacheVault 1U dummy fan kit
CacheVault Installation Kits	MCP-240-00127-0N	-	SuperCap installation kit for thick 2.5" HDD location
	BKT-BBU-BRACKET-05	-	SuperCap installation kit for PCI-E location
Fan	FAN-0101L4	Up to 4	40x40x56 mm, 14.4K-10.7K RPM Counter-rotating Cooling Fan
Onsite Service Program	OS4HR3/2/1	-	3/2/1-year onsite 24x7x4 service
Onsite Service Program	OSNBD3/2/1	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)