

SuperServer 2028TR-H72R



Key Features

Four **hot-pluggable** systems (nodes) in a 2U form factor. Each node supports the following:

1. Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v3 family; QPI up to 9.6GT/s
2. Up to 512GB ECC DDR4 2133MHz; 8x DIMM slots
3. 1x PCI-E 3.0 x16 (LP) slot
4. Intel® i350 Dual port GbE LAN
5. 6x 2.5" Hot-swap SAS2/SATA3 drive bays
6. 1600W Redundant Power Supplies Titanium Level
7. 2x SATA DOM

Available Colors:

Black



Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

Specifications

Product SKUs

SYS-2028TR-H72R ■ SuperServer 2028TR-H72R (Black)

Motherboard

Super X10DRT-H

Processor/Cache

CPU ■ Intel® Xeon® processor E5-2600 v3 family (up to 145W TDP) *
 ■ Dual Socket R3 (LGA 2011)

Cores / Cache ■ Up to 18 Cores / Up to 45MB Cache

System Bus ■ QPI up to 9.6 GT/s

Note * Please contact Supermicro Technical Support for additional information about frequency optimized CPUs and specialized system optimization.

System Memory

Memory Capacity ■ 8x 288-pin DDR4 DIMM slots
 ■ Up to 512GB ECC LRDIMM, 256GB ECC RDIMM

Chassis

Form Factor ■ 2U Rackmount

Model ■ CSE-217HQ-R1K68B

Dimensions and Weight

Width ■ 17.25" (438mm)

Height ■ 3.47" (88mm)

Depth ■ 26.75" (679mm)

Package ■ 26.4" (H) x 11.2" (W) x 39.8" (D)

Weight ■ Gross Weight: 103 lbs (46.7kg)
 ■ Net Weight: 87 lbs (39.5 kg)

Available Colors ■ Black

Front Panel

Buttons ■ Power On/Off button
 ■ System Reset button
 ■ UID button

LEDs ■ Power status LED
 ■ HDD activity LED
 ■ 2x Network activity LEDs
 ■ Universal Information (UID) LED

Expansion Slots (per Node)

Memory Type	<ul style="list-style-type: none"> 2133/1866/1600MHz ECC DDR4 SDRAM 72-bit
DIMM Sizes	<ul style="list-style-type: none"> RDIMM: 32GB, 16GB, 8GB, 4GB LRDIMM: 64GB, 32GB
Memory Voltage	<ul style="list-style-type: none"> 1.2 V
Error Detection	<ul style="list-style-type: none"> Corrects single-bit errors

On-Board Devices

Chipset	<ul style="list-style-type: none"> Intel® C612 Express chipset
SAS	<ul style="list-style-type: none"> SAS2 (6Gbps) via LSI 2208 w/ Hardware RAID support RAID 0, 1, 5, 6, 10, 50 support
SATA	<ul style="list-style-type: none"> SATA3 (6Gbps) with RAID 0, 1
IPMI	<ul style="list-style-type: none"> Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support ASPEED AST2400 BMC
Network Controllers	<ul style="list-style-type: none"> Intel® i350 Dual Port Gigabit Ethernet Virtual Machine Device Queues reduce I/O overhead Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output 1x Realtek RTL8201N PHY (dedicated IPMI)
Video	<ul style="list-style-type: none"> ASPEED AST2400 BMC

Input / Output (per Node)

Serial ATA	<ul style="list-style-type: none"> 8x SATA3 (6Gbps) ports
SAS	<ul style="list-style-type: none"> 6x SAS2 ports (6Gbps)
LAN	<ul style="list-style-type: none"> 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port
USB	<ul style="list-style-type: none"> 2x USB 3.0 ports (rear)
Video	<ul style="list-style-type: none"> 1x VGA port

PCI-Express	<ul style="list-style-type: none"> 1x PCI-E 3.0 (x16) Low-profile slot
-------------	---

Drive Bays (per Node)

Hot-swap	<ul style="list-style-type: none"> 6x 2.5" Hot-swap SAS2/SATA3 drive bays
----------	--

System Cooling

Fans	<ul style="list-style-type: none"> 4x 8cm heavy duty fans with PWM fan speed control
------	---

Power Supply

1600W Titanium Level (96%) High-efficiency Redundant Single Output Power Supplies

AC Input	<ul style="list-style-type: none"> 800W Output @ 100-140V, 7-10A, 50-60Hz 1600W Output @ 180-240V, 8-11A, 50-60Hz
DC Output	<ul style="list-style-type: none"> 800W: +12V/67A, +5Vsb/1A 1600W: +12V/133A, +5Vsb/1A

Certification	 Titanium Level [Test Report]
---------------	--

System BIOS

BIOS Type	<ul style="list-style-type: none"> 128Mb SPI Flash EEPROM with AMI BIOS
BIOS Features	<ul style="list-style-type: none"> Plug and Play (PnP) APM 1.2 PCI 2.2 ACPI 1.0 / 2.0 USB Keyboard support SMBIOS 2.3 UEFI

Operating Environment / Compliance

RoHS	<ul style="list-style-type: none"> RoHS Compliant
Environmental Spec.	<ul style="list-style-type: none"> Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X10DRT-H	4	Super X10DRT-H Motherboard
	CSE-217HQ-R1K68B	1	2U Chassis
Backplane	BPN-ADP-S2208L-H6iR-O-P	4	BPN-ADP-S2208L-H6iR-O-P
Backplane	BPN-SAS-217HQ	1	Support 24x2.5ö SAS/SATA hard drives
Riser Card	RSC-R1UTP-E16R-O-P	4	,RoHS/REACH,PBF
Heatsink / Retention	SNK-P0047PS	4	1U Passive CPU Heat Sink for X9, X10 Systems Equipped w/ a Narrow ILM MB
Heatsink / Retention	SNK-P0047PW	4	1U Passive Custom Rear CPU Heat Sink for X9, X10 1U Twin, 2U Twin^2 8-DIMM per Node Series Servers
Power Supply	PWS-1K68A-1R	2	1U 1600W Redundant Titanium Power Supply 76mm width 27Pair,PBF

Optional Parts List			
	Part Number	Qty	Description
Onsite Service Program	OS4HR3/2/1	-	3/2/1-year onsite 24x7x4 service
Onsite Service Program	OSNBD3/2/1	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)
SuperDOM	-	-	Supermicro SATA DOM Solutions [Details]
Network Card(s)	AOC-S40G-i2Q	-	Standard LP 2-port 40GbE controller, based on Intel Fortville XL710
	AOC-SGP-i2	-	Standard LP, 2x GbE RJ45, PCI-E x4, Intel i350AM2
	AOC-SGP-i4	-	Standard LP, 4x GbE RJ45, PCI-E x4, Intel i350
	AOC-STG-b4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom BCM57840S
	AOC-STGN-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel 82599ES
	AOC-STGN-i1S	-	Standard LP, 1x 10GbE SFP+, PCI-E x8, Intel 82599EN
	AOC-STG-i2T	-	Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel X540
	AOC-STG-i2	-	Standard LP, 2x 10GbE CX4, PCI-E x8, Intel 82598EB
BBU (Battery Backup Unit)	BTR-0018L-0000-LSI	-	Battery Backup for SAS 2108 (can be direct attached to card or connect by extension cable use BTR-0018L-Kit)