

WSX-745TQ High Performance Tower Workstation

Specifications

Chassis

Standard Color

Front Panel Connector

Indicators

Front Panel Controls

Cooling Fan

System Board Specifications

Drive Bays

Expansion Slots

Power Supply

Weight

Dimension (W x H x D)

Operating Temperature

Non-Operating Temperature

Operating Relative Humidity

Non-Operating Relative Humidity

Chassis Features

Tower / 4U Chassis Support

Black

2 x USB 3.0 ports

Power LED, Hard drive activity LED, 2x Network activity LEDs, System Information LED, Power Fail LED

Power On/Off Button
System Reset Button

3 x 5000 RPM Hot-swap PWM Cooling Fans
2 x 5000 RPM Hot-swap Rear Exhaust PWM Fans

Supports Motherboard: X10SAE, X10SAT, X10SRA, X10SRH-CLN4F, X10DAI, X9SRE

3 x 5.25" External Drive Bays
8 x 3.5" Hot-swap SAS/SATA Drive Bays

7 x Expansion Slots

800W 100-240 VAC Power Supply w/ PFC
920W 100-240V AC 80 PLUS Platinum High-Efficiency (94+%) Power Supply with PMBus **(Optional)**
800W Redundant 100-240V AC High-Efficiency Power Supply w/ PFC **(Optional)**
920W Redundant 100-240V AC 80 PLUS Platinum High-Efficiency (94+%) Power Supply with PMBus and I2C **(Optional)**
1200W Redundant 100-240V AC 80 PLUS Gold High-Efficiency Power Supply with PMBus **(Optional)**
1280W Redundant 100-240V AC 80 PLUS Platinum High-efficiency Digital Power Supplies w/ PMBus 1.2 **(Optional)**

62 lbs (28 kg)

7.0" x 17.8" x 25.5" (178 x 452 x 648 mm)

Environmental

41°F ~ 95°F

-40°F ~ 140°F

8% ~ 90% (non-condensing)

5% - 95% (non-condensing)

