

PMS4202 - 17" TFT LCD Fanless Touch Panel PC



Specifications

Item No.	PMS4202
Front Bezel	Plastic ABS
LCD Size	17" SXGA TFT LCD
Touch Screen	5-wire resistive type
Resolution	1280 x 1024
Brightness(cd/m ²)	350 nits
View Angle (H/V)	178°/178°
Chipset	Intel® QM77
CPU	Socket rPGA988B 3rd Generation Intel® Core™ i7/ i5/ i3/ Celeron® processors (Ivy Bridge), TDP up to 35W
System Memory	2 x 204-pin DDR3 SO-DIMM Memory (max. 16GB)
I/O Connector	1 x RS-232/422/485 (isolated 4KV) 2 x 10/100/1000Mbps Ethernet 2 x USB 2.0 (isolated 4KV) 2 x USB 3.0 1 x Audio (Line-out) 1 x Audio (Mic-in) 1 x DisplayPort
Expansion Slot	1 x PCI or 1 x PCIe x4 slot (Optional) 2 x PCIe Mini Card slot
Wireless	1 x 802.11 a/b/g/n Wireless Module (Optional)
Drive Bay	1 x 2.5" SATA HDD 1 x mSATA 1 x Slim DVD+/-RW Optical Drive (Optional)
Speaker	2 x 2W
Camera	1 x 5M pixels camera
Watchdog Timer	255 levels, 0~255 sec.
Function Key	LCD brightness up/down, audio volume up/down, power on/off
Power Supply	External 24VDC with AC/DC medical grade power adapter
Mounting	Wall Mount, VESA Arm and Desktop Stand (Optional)
Operation Temperature	32°F ~ 104°F (0°C ~ 40°C)
Storage Temperature	32°F ~ 104°F (0°C ~ 40°C)
Relative Humidity	20% ~ 90% @ 40°C; non-condensing
Dimensions (WxHxD)	17.24" x 14.81" x 3.01" (438 x 376.4 x 76.5 mm)
Net Weight	22.81 lbs (10.35 Kg)
Certification	CE

PMS4202 - 17" TFT LCD Fanless Touch Panel PC



Mechanical Drawing

