


# SuperStorage Server 2028R-E1CR48N (Complete System On



## Integrated Board



Super X10DSC+

Due to the complexity of integration, this product is sold as completely assembled systems only (with minimum 24 HDDs and 1 NIC or SIOM card).

## Key Features

1. Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4†/ v3 family; QPI up to 9.6GT/s
2. Up to 3TB† ECC 3DS LRDIMM , up to DDR4- 2400†MHz ; 24x DIMM slots
3. 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8
4. SIOM for flexible networking options
5. 48x 2.5" Hot-swap SAS3/SATA3 drive bays
6. Onboard LSI 3108 SAS3 Hardware RAID RAID 0, 1, 5, 6, 10, 50, 60
7. Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
8. 5x 8cm hot-swap redundant PWM fans
9. 1600W Redundant Power Supplies Titanium Level (96%)

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

## Specifications

### Product SKUs

SSG-2028R-E1CR48N	▪ SuperServer 2028R-E1CR48N (Black)
-------------------	-------------------------------------

### Motherboard

Super X10DSC+

### Processor/Cache

CPU	▪ Intel® Xeon® processor E5-2600 v4†/ v3 family (up to 145W TDP) * ▪ Dual Socket R3 (LGA 2011)
-----	---

Cores / Cache	▪ Up to 22 Cores† / Up to 55MB† Cache
---------------	---------------------------------------

System Bus	▪ QPI up to 9.6 GT/s
------------	----------------------

Note	† BIOS version 2.0 or above is required
------	---

Note	* Please contact Supermicro Technical Support for additional information about frequency optimized CPUs and specialized system optimization.
------	--

### Chassis

Form Factor	▪ 2U Rackmount
Model	▪ CSE-226STS-R1K62P1

### Dimensions

Width	▪ 17.2" (437mm)
Height	▪ 3.5" (89mm)
Depth	▪ 30.2" (767mm) ▪ With Cable Management Arm Installed: 35.2" (895mm)
Available Colors	▪ Black

### Front Panel

Buttons	▪ Power On/Off button ▪ System Reset button
LEDs	▪ Power status LED ▪ Hard drive activity LED ▪ 2x Network activity LEDs ▪ System Overheat LED ▪ Power fail LED

## System Memory

Memory Capacity	<ul style="list-style-type: none"><li>24x 288-pin DDR4 DIMM slots</li><li>Up to 3TB<sup>†</sup> ECC 3DS LRDIMM, 768 ECC RDIMM</li></ul>
Memory Type	<ul style="list-style-type: none"><li>2400<sup>†</sup>/2133/1866/1600MHz ECC DDR4 SDRAM 72-bit</li></ul>
DIMM Sizes	<ul style="list-style-type: none"><li>RDIMM: 32GB, 16GB, 8GB, 4GB</li><li>LRDIMM: 64GB, 32GB</li><li>3DS LRDIMM: 128GB</li></ul>
Memory Voltage	<ul style="list-style-type: none"><li>1.2 V</li></ul>
Error Detection	<ul style="list-style-type: none"><li>Corrects single-bit errors</li></ul>

## On-Board Devices

Chipset	<ul style="list-style-type: none"><li>Intel® C612 chipset</li></ul>
SAS3	<ul style="list-style-type: none"><li>LSI 3108 SAS3 onboard</li><li>Hardware RAID 0, 1, 5, 6, 10, 50, 60</li></ul>
SATA	<ul style="list-style-type: none"><li>SATA3 (6Gbps); RAID 0, 1, 5, 10</li></ul>
IPMI	<ul style="list-style-type: none"><li>Support for Intelligent Platform Management Interface v.2.0</li><li>IPMI 2.0 with virtual media over LAN and KVM-over-LAN support</li><li>ASPEED AST2400 BMC</li></ul>
Network Controllers	<ul style="list-style-type: none"><li>SIOM support for flexible networking options</li></ul>
Video	<ul style="list-style-type: none"><li>ASPEED AST2400 BMC</li></ul>

## Input / Output

LAN	<ul style="list-style-type: none"><li>LAN ports via SIOM Add-On-Card: (See <a href="#">SIOM Compatibility Matrix</a>)</li></ul>
USB	<ul style="list-style-type: none"><li>3x USB 3.0 ports (2 rear + 1 Type A)</li></ul>
Video	<ul style="list-style-type: none"><li>1x VGA port</li></ul>
Serial Port / Header	<ul style="list-style-type: none"><li>1x Fast UART 16550 port / 1 Header</li></ul>

## Expansion Slots

PCI- <b>91 dfYgg</b>	<ul style="list-style-type: none"><li>2x PCI-E 3.0 x16 slots</li><li>1x PCI-E 3.0 x8 slots</li></ul>
----------------------	--

## Drive Bays

Hot-swap	<ul style="list-style-type: none"><li>48x 2.5" Hot-swap SAS3/SATA3 drive bays</li><li>2x 2.5" rear Hot-swap drive bays</li></ul>
----------	--

## Backplane

Two 24 port SAS3 12G expander backplanes, each supporting up to 24x 2.5" SAS3 drives

## System Cooling

Fans	<ul style="list-style-type: none"><li>5x 8cm hot-swap redundant PWM cooling fans</li></ul>
------	--

## Power Supply

1600W Redundant Titanium Level AC Power Supplies with PMbus

Input	<ul style="list-style-type: none"><li>100-127 V, 50-60 Hz</li><li>200-240 V, 50-60 Hz</li></ul>
+12V	<ul style="list-style-type: none"><li>Max: 83.3A &amp; Min: 0A (100Vac-127Vac)</li><li>Max: 133A &amp; Min: 0A (200Vac-240Vac)</li></ul>
12V SB	<ul style="list-style-type: none"><li>Max: 2.1A</li><li>Min: 0A</li></ul>

Certification	  Titanium Level Certified [ <a href="#">Test Report</a> ]
---------------	--

## System BIOS

BIOS Type	<ul style="list-style-type: none"><li>128Mb SPI Flash EEPROM with AMI BIOS</li></ul>
BIOS Features	<ul style="list-style-type: none"><li>Plug and Play (PnP)</li><li>APM 1.2</li><li>PCI 2.2</li><li>ACPI 1.0 / 2.0</li><li>USB Keyboard support</li><li>SMBIOS 2.3</li><li>UEFI</li></ul>

## Operating Environment / Compliance

RoHS	<ul style="list-style-type: none"><li>RoHS Compliant</li></ul>
Environmental Spec.	<ul style="list-style-type: none"><li>Operating Temperature: 10°C to 35°C (50°F to 95°F)</li><li>Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)</li><li>Operating Relative Humidity: 8% to 90% (non-condensing)</li><li>Non-operating Relative Humidity: 5% to 95% (non-condensing)</li></ul>

## Parts List

Parts List - (Items Included)			
	Part Number	Qty	Description
<b>Motherboard / Chassis</b>	MBD-X10DSC+	1	Super X10DSC+ Motherboard
	CSE-226STS-R1K62P1	1	2U Chassis
<b>Add-on Card / Module</b>	AOM-S3108M-H8L-P	1	sas3 roc mez for X10dsc
<b>Backplane</b>	BPN-SAS3-226SEL1-N4	2	2U 24-Port Expander Backplane Support 20x2.5" SAS3/SATA3 HDD/SSD and 4x2.5" SAS3/SATA3/NVMe Storage Devices
<b>Cable 1</b>	CBL-SAST-0844	2	SLIMLINE SAS to MiniSAS HD,INT,85CM,30D-41F-14D,no sidebend,32AWG
<b>Cable 2</b>	CBL-SAST-0836	2	MINI SAS HD,INT,SAS3 SSD,48CM,no sidebend,32AWG
<b>Heatsink / Retention</b>	SNK-P0047PS	2	1U Passive CPU Heat Sink for X9, X10 Systems Equipped w/ a Narrow ILM MB
<b>Parts</b>	MCP-220-82609-0N	1	Rear 2.5 x 2 Hot swap HDD kit for 216B/826B/417B/846X/847B
<b>Power Supply</b>	PWS-1K62A-1R	2	AC-DC 1600W, Titanium Level, Redundancy, 1U, DC Output: +12V and +12Vs, 203 x 73.5 x 40 mm, AC Input: 90 - 264 VAC/47-63Hz, PMBus 1.2 with DSP controller,HF,RoHS/REACH
<b>Drive Tray(s)</b>	MCP-220-00047-0B	48	Black 3rd Gen hot-swap 2.5" HDD tray

Optional Parts List			
	Part Number	Qty	Description
<b>3108 Cache Protection</b>	BTR-CV3108-FT1	-	LSI 3108 CacheVault kit (ROHS, Reach)
<b>Onsite Service Program</b>	<a href="#">OS4HR3/2/1</a>	-	3/2/1-year onsite 24x7x4 service
<b>Onsite Service Program</b>	<a href="#">OSNBD3/2/1</a>	-	3/2/1-year onsite NBD service
<b>Software</b>	SFT-OOB-LIC	1	OOB Management Package (per node license)
<b>Software</b>	SFT-DCMS-Single	1	DataCenter Management Package (per node license)
<b>SIOM Network Card(s)</b>	<a href="#">AOC-MGP-I2</a>	-	SIOM 2-port GbE, Intel i350-AM2
	<a href="#">AOC-MGP-I4</a>	-	SIOM 4-port GbE, Intel i350-AM4
	<a href="#">AOC-MTGN-I2S</a>	-	SIOM 2-port 10G SFP+, Intel 82599ES
	<a href="#">AOC-MTG-I4S</a>	-	SIOM 4-port 10G SFP+, Intel XL710