


1027GR-72R2



Available Color:

Black

Key Features

1. Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family†
2. Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM slots
3. 3x PCI-E 3.0 x16 slots (support GPU/Xeon Phi cards, opt.), 1x PCI-E 3.0 x8 (in x16) LP slot
4. Integrated IPMI 2.0 with KVM and Dedicated LAN
5. Intel i350-AM2 Dual port GbE LAN
6. 4x Hot-swap 2.5" SATA3 Drive Bays
7. 1600W Redundant Power Supplies Platinum Level (94%+)
8. 10x Counter rotating fans w/ optimal fan speed control
9. Smart server management tools
10. LSI 2208 SAS controller

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

Specifications

Product SKUs

SYS-1027GR-72R2 ■ SuperServer 1027GR-72R2 (Black)

Motherboard

[Super X9DRG-HF+11](#)

Processor/Cache

CPU ■ Dual Socket R (LGA 2011)
 ■ Intel® Xeon® processor E5-2600 and E5-2600 v2 family† (up to 130W TDP)

Note † BIOS version 3.0 or above is required

Cache ■ Up to 30MB

System Bus ■ QPI up to 8 GT/s

[GPU/Xeon Phi Support](#) ■ M2090, up to 130W CPU at 30°C
 ■ M2075, up to 130W CPU at 35°C
 ■ K10/K20/K20X/K1/K2 (Kepler), up to 130W CPU at 30°C
 ■ Xeon Phi, up to 130W CPU at 30°C

System Memory

Chassis

Form Factor ■ 1U Rackmount

Model ■ CSE-118GH-R1K66B

Dimensions

Height ■ 1.7" (43mm)

Width ■ 17.2" (437mm)

Depth ■ 30.6" (777mm)

Gross Weight ■ 48 lbs (21.8 kg)

Available Color ■ Black

Front Panel

Buttons ■ Power On/Off button
 ■ System Reset button

LEDs ■ Power LED
 ■ Hard drive activity LED
 ■ 2x Network activity LEDs
 ■ System Overheat LED / Fan fail LED / UID LED

Expansion Slots

Memory Capacity	<ul style="list-style-type: none"> 16x 240-pin DDR3 DIMM slots Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM) Up to 128GB DDR3 ECC and non-ECC UDIMM
Memory Type	<ul style="list-style-type: none"> 1866/1600/1333/1066MHz ECC DDR3 SDRAM 72-bit, 240-pin gold-plated DIMMs
DIMM Sizes	<ul style="list-style-type: none"> 32GB, 16GB, 8GB, 4GB, 2GB, 1GB
Memory Voltage	<ul style="list-style-type: none"> 1.5 V, 1.35 V
Error Detection	<ul style="list-style-type: none"> Corrects single-bit errors Detects double-bit errors (using ECC memory)

On-Board Devices

Chipset	<ul style="list-style-type: none"> Intel® C602 Chipset
SATA	<ul style="list-style-type: none"> SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1
SAS	<ul style="list-style-type: none"> SAS2 (6Gbps) via LSI 2208 AOC-S2208-E16AR+II HW RAID 0, 1, 5, 10 support
IPMI	<ul style="list-style-type: none"> Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support Nuvoton WPCM450 BMC
Network Controllers	<ul style="list-style-type: none"> Intel® i350-AM2 Dual Port Gigabit Ethernet Virtual Machine Device Queues reduce I/O overhead Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output
Graphics	<ul style="list-style-type: none"> Nuvoton WPCM450 BMC

Input / Output

SATA	<ul style="list-style-type: none"> 2x SATA3 (6Gbps) ports 2x SATA2 (3Gbps) ports
SAS	<ul style="list-style-type: none"> 4x HW RAID SAS2 (6Gbps) ports
LAN	<ul style="list-style-type: none"> 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port
USB	<ul style="list-style-type: none"> 2x USB 2.0 ports
Video	<ul style="list-style-type: none"> 1x VGA Connector
Serial Port	<ul style="list-style-type: none"> 1x Serial header

System BIOS

BIOS Type	<ul style="list-style-type: none"> 16Mb SPI Flash EEPROM with AMI® BIOS
BIOS Features	<ul style="list-style-type: none"> Plug and Play (PnP) APM 1.2 DMI 2.3 PCI 2.3 ACPI 1.0 / 2.0 / 3.0 USB Keyboard support SMBIOS 2.7.1 UEFI

PCI-Express	<ul style="list-style-type: none"> 3x PCI-E 3.0 x16 slots (support GPU/Xeon Phi cards, optional) 1x PCI-E 3.0 x8 (in x16) low-profile slot
-------------	--

Drive Bays

Hot-swap	<ul style="list-style-type: none"> 4x 2.5" Hot-swap SAS/SATA drive bays
----------	--

Backplane

SAS/SATA HDD Backplane	
------------------------	--


System Cooling

Fans	<ul style="list-style-type: none"> 10x counter-rotating fans with optimal fan speed control
------	--

Power Supply

1000W/1600W 1U Redundant Power Supply	
---------------------------------------	--

AC Input	<ul style="list-style-type: none"> 1000W @ 100-127V, 12.9A Max., 50-60Hz 1600W @ 200-240V, 9.5A Max., 50-60Hz
DC Output	<ul style="list-style-type: none"> 1000W: +12V/82A; +12Vsb/2A 1600W: +12V/132A; +12Vsb/2A

Certification	  Platinum Level [Test Report]
---------------	--

PC Health Monitoring

CPU	<ul style="list-style-type: none"> Monitors for CPU Cores, +1.5V, +3.3V, +5V, +12V, +5 Stdby, +3.3 Stdby, VBAT, Memory Voltages. CPU Core 6-Phase-switching voltage regulator
FAN	<ul style="list-style-type: none"> Total of ten 4-pin PWM fans 10x fans with tachometer monitoring Status monitor for speed control Status monitor for on/off control Low noise fan speed control
Temperature	<ul style="list-style-type: none"> Monitoring for CPU and chassis environment CPU thermal trip support Thermal Control for 10x Fan Connectors PSU I²C temperature sensing logic Thermal Monitor 2 (TM2) support PECI
LED	<ul style="list-style-type: none"> Power Fail / Overheat LED Suspend-state Indicator LED UID LED
Other Features	<ul style="list-style-type: none"> SDDC Support

Operating Environment / Compliance

RoHS	<ul style="list-style-type: none"> RoHS Compliant
Environmental Spec.	<ul style="list-style-type: none"> Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)			
	Part Number	Qty	Description
Motherboard / Chassis	MBD-X9DRG-HF+II	1	Super X9DRG-HF+II Motherboard
	CSE-118GH-R1K66B	1	1U Black SC118GQ Chassis
Air Shroud	MCP-310-11802-0N	1	Air Shroud for X9DRG-HF used in SC118GQ-R1800B
Backplane	BPN-SAS-118G-4	1	SAS-118G-4; supports 4X2.5" SATA HDD,
Cable 1	CBL-0157L-01	1	8 pin to 8 pin ribbon SGPIO cable with tube, 60cm, PBF
Cable 2	CBL-0460L	1	8 Pin to Two 4 Pin Backplane Power Ext. 28/22cm. 18AWG
Cable 3	CBL-PWEX-0582	3	8 pin to two 6+2 pin 12V GPU power cable, 30 cm 16/20 AWG,HF,RoHS/REACH,PBF
Cable 4	CBL-0473L	4	21cm 30AWG SATA S-S cable
Cable 5	CBL-0296L	5	4 pin to 4 pin fan extension cord, for PWM fan. 23cm. 24AWG
Riser Card	RSC-R1UG-E16R+II	1	R1UG-E16R+II
Riser Card	RSC-R1UG-E16A+II	1	R1UG-E16A+II
Riser Card	RSC-R1UG-AE16B+II	1	RSC-R1UG-AE16B+II
Heatsink / Retention	SNK-P0047PS	1	1U Passive CPU Heat Sink for X9, X10 Systems Equipped w/ a Narrow ILM MB
Heatsink / Retention	SNK-P0047PSC	1	1U Passive Front CPU Heat Sink w/ a Side Air Channel for X9, X10 Systems Equipped with a Narrow ILM MB
Add-on Card	AOC-S2208-E16AR+II-O-P	1	AOC with LSI 2208