

SuperServer F618R2-RC0+



Key Features

8 Hot-plug System Nodes in 4U Each node supports:

1. Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4[†]/ v3 family; QPI up to 9.6GT/s
2. Up to 2TB[†] ECC 3DS LRDIMM , up to DDR4- 2400[†]MHz ; 16x DIMM slots
3. Expansion slots: 1 PCI-E 3.0 x16 (LP)
1 PCI-E 3.0 x8 (Micro Low Profile)
4. I/O ports: 2 GbE ports, 1 VGA,
2 USB 3.0 ports
5. Built-in Server management tool (IPMI 2.0, KVM/media over LAN) with dedicated LAN port
6. 6x 2.5" Hot-swap SAS/SATA or
4x 2.5"Hot-swap SAS/SATA +
2x SAS/SATA/NVMe hybrid;
SAS3 via LSI 3008
7. 3x heavy duty internal fans
8. 2000W High efficiency (96%)
Redundant PSU; Titanium Level

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

Specifications

Product SKUs

- SYS-F618R2-RC0+ ■ SuperServer F618R2-RC0+ (Black)

Motherboard

Super X10DRFR-N

Processor/Cache

- CPU ■ Intel® Xeon® processor E5-2600 v4[†]/ v3 family (up to 145W TDP) *
■ Dual Socket R3 (LGA 2011)

- Cores / Cache ■ Up to 22 Cores[†] / Up to 55MB[†] Cache

- System Bus ■ QPI up to 9.6 GT/s

Note [†] BIOS version 2.0 or above is required

Note * Please contact Supermicro Technical Support for additional information about frequency optimized CPUs and specialized system optimization.

Chassis

- Form Factor ■ 4U Rackmount
Model ■ CSE-F418BC-R2K04B

Dimensions and Weight

- Width ■ 17.63" (448mm)
Height ■ 6.96" (177mm)
Depth ■ 29" (737mm)
Package ■ 28.3" (W) x 15.0" (H) x 42.4" (D)
Weight ■ Net Weight: 150 lbs (68.04 kg)
■ Gross Weight: 200 lbs (90.71 kg)
Available Colors ■ Black

Front Panel

- Buttons ■ Power On/Off button
■ UID button
LEDs ■ Power status LED
■ Hard drive activity LED
■ 2x Network activity LEDs
■ Information LED (UID, Fan failure, Overheat)

System Memory	
Memory Capacity	<ul style="list-style-type: none"> 16x 288-pin DDR4 DIMM slots Up to 2TB[†] ECC 3DS LRDIMM, 1TB ECC RDIMM
Memory Type	<ul style="list-style-type: none"> 2400[†]/2133/1866/1600MHz ECC DDR4 SDRAM 72-bit
DIMM Sizes	<ul style="list-style-type: none"> RDIMM: 64GB, 32GB, 16GB, 8GB, 4GB LRDIMM: 64GB, 32GB 3DS LRDIMM: 128GB
Memory Voltage	<ul style="list-style-type: none"> 1.2 V
Error Detection	<ul style="list-style-type: none"> Corrects single-bit errors

On-Board Devices	
Chipset	<ul style="list-style-type: none"> Intel® C612 chipset
SAS	<ul style="list-style-type: none"> LSI 3008 SAS3 (12Gbps) controller
SATA	<ul style="list-style-type: none"> SATA3 (6Gbps) with RAID 0, 1, 5, 10
IPMI	<ul style="list-style-type: none"> Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support ASPEED AST2400 BMC
Network Controllers	<ul style="list-style-type: none"> Intel® i350-AM2 Dual Port Gigabit Ethernet Virtual Machine Device Queues reduce I/O overhead Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output 1x Realtek RTL8201N PHY (dedicated IPMI)
Graphics	<ul style="list-style-type: none"> ASPEED AST2400 BMC

Input / Output (per node)	
SAS	<ul style="list-style-type: none"> 6x SAS3 (12Gbps) ports
LAN	<ul style="list-style-type: none"> 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port
USB	<ul style="list-style-type: none"> 2x USB 3.0 ports
VGA	<ul style="list-style-type: none"> 1x VGA port

Management	
Software	<ul style="list-style-type: none"> Intel® Node Manager SuperDoctor® 5 Watch Dog NMI IPMI 2.0 SUM and SSM
Power Configurations	<ul style="list-style-type: none"> ACPI / APM Power Management Power-on mode for AC power recovery

Expansion Slots (per node)	
PCI-Express	<ul style="list-style-type: none"> 1x PCI-E 3.0 x16 Low-profile 1x PCI-E 3.0 x8 (Micro LP) MicroLP Adapter Matrix (Networking options)

Drive Bays (per node)	
Hot-swap	<ul style="list-style-type: none"> 6x 2.5" Hot-swap SAS/SATA drives Optional NVMe support

Backplane	
1x SAS/SATA backplane	

System Cooling (per node)	
Fans	<ul style="list-style-type: none"> 3x 4cm 14k RPM middle fans

Power Supply with Digital Switching Control	
2000W Redundant Titanium Level Power Supplies	
Total Output Power	<ul style="list-style-type: none"> 1000W/1800W/1980W/2000W
AC Input	<ul style="list-style-type: none"> 100-127 V, 50-60 Hz 200-220 V, 50-60 Hz 220-230 V, 50-60 Hz 230-240 V, 50-60 Hz
+12V	<ul style="list-style-type: none"> Max: 83.3A & Min: 0A (100Vac-127Vac) Max: 150A & Min: 0A (200Vac-220Vac) Max: 165A & Min: 0A (220Vac-230Vac) Max: 166.7A & Min: 0A (230Vac-240Vac)
5V SB	<ul style="list-style-type: none"> Max: 1A / Min: 0A

Certification	  Titanium Level [Test Report]
---------------	--

System BIOS	
BIOS Type	<ul style="list-style-type: none"> 128Mb SPI Flash EEPROM with AMI BIOS
BIOS Features	<ul style="list-style-type: none"> Plug and Play (PnP) APM 1.2 PCI 2.2 ACPI 1.0 / 2.0 USB Keyboard support SMBIOS 2.3 UEFI

Operating Environment / Compliance	
RoHS	<ul style="list-style-type: none"> RoHS Compliant
Environmental Spec.	<ul style="list-style-type: none"> Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X10DRFR-N	8	Super X10DRFR-N Motherboard
	CSE-F418BC-R2K04B	1	4U Chassis
Backplane	BPN-ADP-8S3008-1UF	8	BPN-ADP-8S3008-1UF
Backplane	BPN-ADP-F418LS	8	Power Distribution Board for X10DRFR,RoHS/REACH,PBF
Backplane	BPN-SAS3-F418-B6N2	8	6-Port Backplane support 4 x 2.5" 12Gb/s SAS/SATA HDD/SSD and 2x SAS/SATA/NVMe Storage Devices,HF,RoHS/REACH
Cable 1	CBL-SAST-0697	16	Internal Mini-SAS HD to Mini-SAS HD 6cm,30AWG,12Gb/s [Amphenol],RoHS/REACH
Cable 2	CBL-0486L	16	2x2 to 2x2 15cm power cable HF. 18AWG
Cable 3	CBL-OTHR-0022L	8	20 to 20 pin cable for BPN-ADP-F418LS,7.5cm, 28AWG,RoHS/REACH,PBF
Label	LBL-0108	1	CAUTION LABEL FOR REDUNDANT PWR SYSTEMS
Manual	MNL-1764-QRG	1	Quick Reference Guide for F618R2-RC0+/ RC0PT+
Riser Card	RSC-R1UF-E16R	8	1U RHS Riser Card with PCI-E X16 for FAT TWIN System
Heatsink / Retention	SNK-P0047PSM	8	1U Passive Front CPU Heat Sink w/ a Middle Air Channel for X9, X10 2U Twin^2+ and Twin Pro^2 Series Servers
Heatsink / Retention	SNK-P0057P	8	1U High Performance Passive CPU Heat Sink for X9, X10 Systems Equipped w/ a Square ILM MB
Power Supply	PWS-2K04A-1R	4	AC-DC 2000W, Titanium Level, Redundancy, 1U, PMBus 1.2, +12V/+5Vsb, 360x76x40mm,HF,RoHS/REACH

Optional Parts List

	Part Number	Qty	Description
NVMe Cable	CBL-SAST-0698	2/node	10cm NVMe cable; RA-RA
Software	SFT-OOB-LIC	8	OOB Management Package (per node license)
Software	SFT-DCMS-Single	8	DataCenter Management Package (per node license)