

# SuperServer 6028U-E1CNRT+ (Complete System Only)



Due to the complexity of integration, this product is sold as completely assembled systems only (with minimum 2 CPU and 4 DIMM). Please contact your Supermicro sales rep for special requirements.

## Key Features

- Flexible Connectivity Options

1. Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4†/ v3 family; QPI up to 9.6GT/s
2. Up to 3TB† ECC 3DS LRDIMM , up to DDR4- 2400†MHz ; 24x DIMM slots
3. Up to 7x PCI-E 3.0 x8 slots (up to 5x FH, 10.5" L, 1x LP, 1x Internal LP)
4. 2x 10GBase-T ports
5. 12x Hot-swap 3.5" Drive Bays: Default 4x NVMe ports; 12x SAS3 ports via Expander and AOC: AOC-S3108L-H8iR-16DD, AOC-S3108L-H8iR, AOC-S3008L-L8e, AOC-S3008L-L8i
6. 4x heavy duty fans w/ optimal fan speed control
7. 1000W High efficiency (96%) Redundant PSU; Titanium Level

Note: Image above may show a varied configuration or optional parts. Please refer to parts list for standard parts included.

## Specifications

### Product SKUs

SYS-6028U-E1CNRT+ ■ SuperServer 6028U-E1CNRT+ (Black)

### Motherboard

Super X10DRU-i+

### Processor/Cache

CPU ■ Intel® Xeon® processor E5-2600 v4†/ v3 family (up to 160W TDP) \*  
 ■ Dual Socket R3 (LGA 2011)

Cores / Cache ■ Up to 22 Cores† / Up to 55MB† Cache

System Bus ■ QPI up to 9.6 GT/s

Note † BIOS version 2.0 or above is required

Note \* Please contact Supermicro Technical Support for additional information about frequency optimized CPUs and specialized system optimization.

### Chassis

Form Factor ■ 2U Rackmount

Model ■ CSE-829UE1C4-R1K02

### Dimensions and Weight

Width ■ 17.2" (437mm)

Height ■ 3.5" (89mm)

Depth ■ 28.46" (723mm)

Weight ■ Net Weight: 36 lbs (16.4 kg)  
 ■ Gross Weight: 72 lbs (32.7 kg)

Available Colors ■ Black

### Front Panel

Buttons ■ Power On/Off button  
 ■ System Reset button

LEDs ■ Power status LED  
 ■ HDD activity LED  
 ■ 2x Network activity LEDs  
 ■ System information (overheat/UID) LED

## System Memory

Memory Capacity	<ul style="list-style-type: none"><li>24x 288-pin DDR4 DIMM slots</li><li>Up to 3TB<sup>†</sup> ECC 3DS LRDIMM, 768GB ECC RDIMM</li></ul>
Memory Type	<ul style="list-style-type: none"><li>2400<sup>†</sup>/2133/1866/1600MHz ECC DDR4 SDRAM 72-bit</li></ul>
DIMM Sizes	<ul style="list-style-type: none"><li>64GB, 32GB, 16GB, 8GB, 4GB</li></ul>
Memory Voltage	<ul style="list-style-type: none"><li>1.2 V</li></ul>
Error Detection	<ul style="list-style-type: none"><li>Corrects single-bit errors</li></ul>

## On-Board Devices

Chipset	<ul style="list-style-type: none"><li>Intel® C612 chipset</li></ul>
SATA	<ul style="list-style-type: none"><li>SATA3 (6Gbps) with RAID 0, 1, 5, 10</li></ul>
IPMI	<ul style="list-style-type: none"><li>Support for Intelligent Platform Management Interface v.2.0</li><li>IPMI 2.0 with virtual media over LAN and KVM-over-LAN support</li><li>ASPEED AST2400 BMC</li></ul>
Network Connectivity	<ul style="list-style-type: none"><li>2x 10GBase-T ports via <a href="#">AOC-2UR8N4-i2XT</a></li><li>Intel® X540 10GBase-T</li><li>1x Realtek RTL8211E PHY (dedicated IPMI)</li></ul>
Graphics	<ul style="list-style-type: none"><li>ASPEED AST2400 BMC</li></ul>

## Input / Output

SAS	<ul style="list-style-type: none"><li>12x SAS3 ports support via expander and storage Add-on Cards</li><li>One of the following storage Add-on cards required:<ul style="list-style-type: none"><li>AOC-S3108L-H8iR-16DD (12Gbps SAS3/RAID 0, 1, 5, 6, 10, 50, 60, 2GB DDR3 cache, PCI-E Gen3 16 HDD)</li><li>AOC-S3108-H8iR (12Gbps SAS3/RAID 0, 1, 5, 6, 10, 50, 60, 2GB DDR3 cache, PCI-E Gen3)</li><li>AOC-S3008L-L8i (12Gbps SAS3/RAID 0,1 and 10, PCI-E Gen3)</li><li>AOC-S3008L-L8e (12Gbps SAS3/HBA, PCI-E Gen3)</li></ul></li></ul>
NVMe	<ul style="list-style-type: none"><li>4x NVMe ports</li></ul>
LAN	<ul style="list-style-type: none"><li>2x RJ45 10GBase-T LAN ports</li><li>1x RJ45 Dedicated IPMI LAN port</li></ul>
USB	<ul style="list-style-type: none"><li>5x USB 3.0 ports (2 rear, 2 onboard header, 1 Type A)</li></ul>
Video	<ul style="list-style-type: none"><li>1x VGA Connector</li></ul>
Serial Port / Header	<ul style="list-style-type: none"><li>1x Serial header</li></ul>
DOM	<ul style="list-style-type: none"><li>2x SuperDOM (Disk on Module) ports</li></ul>

## System BIOS

BIOS Type	<ul style="list-style-type: none"><li>128Mb SPI Flash EEPROM with AMI BIOS</li></ul>
BIOS Features	<ul style="list-style-type: none"><li>Plug and Play (PnP)</li><li>APM 1.2</li><li>PCI 2.3</li><li>ACPI 1.0 / 2.0 / 3.0 / 4.0</li><li>USB Keyboard support</li><li>SMBIOS 2.7.1</li></ul>

## Expansion Slots

PCI-Express	<ul style="list-style-type: none"><li>Up to 7x PCI-E 3.0 x8 slots (up to 5x FH, 10.5" L, 1x LP, 1x Internal LP)</li></ul> <p>(Both CPUs need to be installed for full access to PCI-E slots and onboard controllers. See manual block diagram and <a href="#">AOC Support</a> for details.)</p>
-------------	---



## Drive Bays

Hot-swap	<ul style="list-style-type: none"><li>12x 3.5" Hot-swap drive bays</li><li>Default 4x NVMe ports</li><li>12x SAS3 ports via Expander and AOC</li></ul> <p>Note: Storage Add-on card is required</p>
----------	---

## System Cooling

Fans	<ul style="list-style-type: none"><li>4x 8cm heavy duty PWM fans</li></ul>
------	--

## Power Supply

1000W Redundant Power Supplies with PMBus	
Total Output Power	<ul style="list-style-type: none"><li>800W/1000W</li></ul>
Dimension (W x H x L)	<ul style="list-style-type: none"><li>73.5 x 40 x 203 mm</li></ul>
Input	<ul style="list-style-type: none"><li>100-127Vac / 9.8 - 7A / 50-60Hz</li><li>200-240Vac / 7 - 5A / 50-60Hz</li></ul>
+12V	<ul style="list-style-type: none"><li>Max: 66.7A / Min: 0A (100-127Vac)</li><li>Max: 83A / Min: 0A (200-240Vac)</li></ul>
12Vsb	<ul style="list-style-type: none"><li>Max: 2.1A / Min: 0A</li></ul>
Output Type	<ul style="list-style-type: none"><li>25 Pairs Gold Finger Connector</li></ul>
Certification	  UL/cUL/CB/BSMI/CE/CCC Titanium Level [ <a href="#">Test Report</a> ]

## PC Health Monitoring

Voltage	<ul style="list-style-type: none"><li>Monitors for CPU Cores, +1.8V, +3.3V, +5V, +12V, +3.3V Standby, +5V Standby, VBAT, Memory Voltages.</li><li>5+1 Phase-switching voltage regulator</li></ul>
FAN	<ul style="list-style-type: none"><li>8x 4-pin fan headers</li><li>Status monitor for speed control</li><li>Pulse Width Modulated (PWM) fan connectors</li></ul>
Temperature	<ul style="list-style-type: none"><li>Support to monitor Supermicro AOC temperatures from IPMI or SD 5</li><li>Monitoring for CPU and chassis environment</li><li>CPU thermal trip support</li><li>Thermal Control for 8x Fan Connectors</li><li>Thermal Monitor 2 (TM2) support</li><li>PECI</li></ul>
LED	<ul style="list-style-type: none"><li>Memory DIMM ECC error LEDs</li><li>CPU / System Overheat LED</li><li>Suspend static indicator LED</li><li>UID/Remote UID</li></ul>
Other Features	<ul style="list-style-type: none"><li>4x 8-pin GPU power connectors</li><li>Chassis intrusion detection</li><li>Chassis intrusion header</li><li>SDDC Support</li></ul>

- UEFI 2.3.1

## Management

Software	<ul style="list-style-type: none"> <li>▪ SuperDoctor® 5</li> <li>▪ Intel® Node Manager 3.0</li> <li>▪ Watch Dog</li> <li>▪ NMI</li> <li>▪ SUM and SSM</li> <li>▪ Optional IPMI 1.5 / 2.0</li> </ul>
Power Configurations	<ul style="list-style-type: none"> <li>▪ ACPI Power Management</li> <li>▪ Power-on mode for AC power recovery</li> </ul>

- RoHS

## Operating Environment / Compliance

RoHS	<ul style="list-style-type: none"> <li>▪ RoHS Compliant</li> </ul>
Environmental Spec.	<ul style="list-style-type: none"> <li>▪ Operating Temperature: 10°C to 35°C (50°F to 95°F)</li> <li>▪ Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)</li> </ul>
	<ul style="list-style-type: none"> <li>▪ Operating Relative Humidity: 8% to 90% (non-condensing)</li> <li>▪ Non-operating Relative Humidity: 5% to 95% (non-condensing)</li> </ul>

## Parts List

### Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X10DRU-i+	1	Super X10DRU-i+ Motherboard
	CSE-829UE1C4-R1K02	1	2U Chassis
Add-on Card / Module	AOC-2UR8N4-I2XT	1	2U Ultra Riser based on Intel X540 controller with 2 10Gbase-T ports, 4 NVMe ports, 1 internal PCI-E x8 3.0 slot, and 1 PCI-E x8 3.0 (in x16 slot)
Air Shroud	MCP-310-82912-0N	1	
Backplane	BPN-SAS3-826EL1-N4	1	12-Port 2U Backplane with Expander support up to 8 x 3.5" SAS3/SATA3 HDD/SDD and 4 x SAS3/SATA3/NVMe Storage Devices, HF, RoHS/REACH
Cable 1	CBL-PWEX-0673	1	8 pin female to 2x big 4 pin female power, 65/70CM, 18AWG, RoHS/REACH
Cable 2	CBL-PWEX-0652	1	8 pin female to 2x RA(Right Angle) big 4 pin female power, 60/65CM, 18AWG, RoHS/REACH
Cable 3	CBL-SAST-0593	2	Internal Mini-SAS HD to Mini-SAS HD 60cm, 30AWG, 12Gb/s, HF, RoHS/REACH, PBF
Cable 4	CBL-SAST-0658	4	Internal Mini-SAS HD cable for PCIe SSD NVMe, 12Gb/s, 60cm, 30AWG, RoHS/REACH
Parts	MCP-240-82909-0N	1	Ultra I/O bracket for SC829U, 219U (i2XT), RoHS/REACH
Drive Tray(s)	MCP-220-00116-0B	4	Black gen-5 3.5-to-2.5 NVMe drive tray, Orange tab (for hotswap NVMe drive), RoHS/REACH
Label	LBL-0108	1	CAUTION LABEL FOR REDUNDANT PWR SYSTEMS
Manual	MNL-1751-QRG	1	SYS-6028U-E1CNR(4)T+, QRG, HF, RoHS/REACH
Riser Card	RSC-R1UW-E8R	1	RSC-R1UW-E8R-O-P
Riser Card	RSC-R2UW-4E8	1	RSC-R2UW-4E8-O-P
Heatsink / Retention	SNK-P0058PSU	2	2U Passive CPU Heat Sink for X10 2U 24-DIMM Ultra Series Servers, RoHS/REACH
Power Supply	PWS-1K02A-1R	2	1U 1000W Redundant Power Supply 73.5mm width Titanium Level, RoHS/REACH
Mounting Rails	MCP-290-00053-0N	1	Inner/outer rail set, quick-release type, 26.5" to 36.4"
	MCP-290-00060-0N	1	Threaded rail adapter default for round hole rack

Optional Parts List			
	Part Number	Qty	Description
<b>Mounting Rails</b>	MCP-290-00053-0N	-	Inner/outer rail set, quick-release type, 26.5" to 36.4"
	MCP-290-00060-0N	-	Threaded rail adapter default for round hole rack
<b>Storage Control Card and Cable(s)</b>	AOC-S3008L-L8e	-	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 122HDD, HBA
	AOC-S3008L-L8i	-	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 63HDD, RAID 0,1,1E
	AOC-S3108L-H8iR	-	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60
	AOC-S3108L-H8iR-16DD	-	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 16HDD, RAID 0, 1, 5, 6, 10, 50, 60
<b>Network Card(s)</b>	AOC-S40G-i2Q	-	Standard LP 2-port 40GbE controller, based on Intel Fortville XL710
	AOC-SGP-i2	-	Standard LP, 2x GbE RJ45, PCI-E x4, Intel i350AM2
	AOC-SGP-i4	-	Standard LP, 4x GbE RJ45, PCI-E x4, Intel i350
	AOC-STG-b4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom BCM57840S
	AOC-STGN-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel 82599ES
	AOC-STGN-i1S	-	Standard LP, 1x 10GbE SFP+, PCI-E x8, Intel 82599EN
	AOC-STG-i2T	-	Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel X540
	AOC-STG-i2	-	Standard LP, 2x 10GbE CX4, PCI-E x8, Intel 82598EB
<b>CacheVault(s)</b>	BTR-CV3108-U1	-	CacheVault for LSI 3108 with Supercap mounting for 2U Ultra
	BTR-TFM8G-LSICVM02 & BKT-BBU-BRACKET-05	-	CacheVault for LSI 3108; Supercap mounting bracket for PCI-E location
	BTR-TFM8G-LSICVM02 & MCP-240-00127-0N	-	CacheVault for LSI 3108; Supercap mounting bracket for 2.5" HDD location
<b>Hot-swap 3.5" to 2.5" Hard Disk Drive Tray</b>	MCP-220-00043-0N	-	Black hot-swap 3.5" to 2.5" HDD tray
<b>Global Services &amp; Support</b>	<a href="#">OS4HR3/2/1</a>	-	3/2/1-year onsite 24x7x4 service
	<a href="#">OSNBD3/2/1</a>	-	3/2/1-year onsite NBD service
<b>Software</b>	SFT-OOB-LIC	1	OOB Management Package (per node license)
<b>Software</b>	SFT-DCMS-Single	1	DataCenter Management Package (per node license)