


SuperServer 2027PR-DC0FR



Available Colors:

Black



Key Features

Two **hot-pluggable** systems (nodes) in a 2U form factor. Each node supports the following:

1. Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family†
2. Up to 1TB ECC LRDIMM, 512GB ECC RDIMM, up to 1866MHz; 16x DIMM sockets
3. 1x PCI-E 3.0 x16 Low-profile slot; 1x PCI-E 3.0 x8 Low-profile slot
4. Intel® i350 Dual port GbE LAN
5. Integrated IPMI 2.0 with KVM and Dedicated LAN
6. Single port IB (FDR, 56 Gbps), w/ QSFP connector
7. 12x Hot-swap 2.5" SAS/SATA HDD Bays
8. LSI 3008 SAS3 controller (8 ports) + 2 SATA3 + 2 SATA2; RAID 0,1,10
9. 1280W Redundant Power Supplies Platinum Level (94%)

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

Specifications

Product SKUs

SYS-2027PR-DC0FR ■ SuperServer 2027PR-DC0FR (Black)

Motherboard

Super X9DRT-PIBF

Processor/Cache

CPU ■ Dual Socket R (LGA 2011)
 ■ Intel® Xeon® processor E5-2600 and E5-2600 v2 family†
 (up to 135W TDP *)
 * Please contact your Supermicro sales representative for additional details

Note † BIOS version 3.0 or above is required

Cache ■ Up to 30MB

System Bus ■ QPI up to 8 GT/s

Chassis

Form Factor ■ 2U Rackmount

Model ■ CSE-217HD+-R1K28B

Dimensions

Width ■ 17.25" (438mm)

Height ■ 3.47" (88mm)

Depth ■ 28.75" (730mm)

Gross Weight ■ 66 lbs (29.9kg)

Available Colors ■ Black

Front Panel

Buttons ■ Power On/Off button
 ■ UID button

LEDs ■ Power status LED
 ■ HDD activity LED
 ■ 2x Network activity LEDs
 ■ Universal Information (UID) LED

System Memory (per Node)

Memory Capacity	<ul style="list-style-type: none">16x 240-pin DDR3 DIMM slotsUp to 1TB DDR3 ECC LRDIMMUp to 512GB DDR3 ECC Registered memory (RDIMM)
Memory Type	<ul style="list-style-type: none">1866/1600/1333/1066/800MHz ECC DDR3 SDRAM 72-bit, 240-pin gold-plated DIMMs
DIMM Sizes	<ul style="list-style-type: none">32GB, 16GB, 8GB, 4GB, 2GB, 1GB
Memory Voltage	<ul style="list-style-type: none">1.5 V, 1.35 V
Error Detection	<ul style="list-style-type: none">Corrects single-bit errorsDetects double-bit errors (using ECC memory)

On-Board Devices

Chipset	<ul style="list-style-type: none">Intel® C602 Chipset
Infiniband	<ul style="list-style-type: none">Mellanox ConnectX-3 FDR Infiniband 56Gb/s Controller
SAS	<ul style="list-style-type: none">LSI 3008 SAS3 (12Gbps) controller; RAID 0, 1, 10 supportNote: In order to support the LSI RAID Controllers, both CPU socket must be populated
SATA	<ul style="list-style-type: none">SATA w/ RAID 0, 1, 5, 10 support, maximum speed of the drive will go with port interface
IPMI	<ul style="list-style-type: none">Support for Intelligent Platform Management Interface v.2.0IPMI 2.0 with virtual media over LAN and KVM-over-LAN supportNuvoton WPCM450 BMC
Network Controllers	<ul style="list-style-type: none">Intel® i350 Dual Port Gigabit EthernetVirtual Machine Device Queues reduce I/O overheadSupports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output1x Realtek RTL8201N PHY (dedicated IPMI)
Graphics	<ul style="list-style-type: none">Matrox G200eW

Input / Output (per Node)

SATA	<ul style="list-style-type: none">2x SATA3 (6Gbps) ports2x SATA2 (3Gbps) ports
SAS	<ul style="list-style-type: none">8x SAS3 (12Gbps) ports
LAN	<ul style="list-style-type: none">2x RJ45 Gigabit Ethernet LAN ports1x RJ45 Dedicated IPMI LAN port
Infiniband	<ul style="list-style-type: none">1x external QSFP Infiniband connector
USB	<ul style="list-style-type: none">2x USB 2.0 ports total (2x rear)
VGA	<ul style="list-style-type: none">1x VGA port
Serial Port / Header	<ul style="list-style-type: none">1x Fast UART 16550 port / 1 Header (internal)
Others	<ul style="list-style-type: none">1x <u>mSATA</u> (full size) and one SATADOM support on the daughter card1x <u>SATADOM</u> support on the motherboard

Expansion Slots (per Node)

PCI-Express	<ul style="list-style-type: none">1x PCI-E 3.0 (x16) Low-profile slot1x PCI-E 3.0 (x8) Low-profile slot
-------------	--

Drive Bays (per Node)

Hot-swap	<ul style="list-style-type: none">12x 2.5" Hot-swap SAS/SATA HDD trays
----------	--

System Cooling

Fans	<ul style="list-style-type: none">4x 8cm heavy duty PWM fans with optimal fan speed control
------	---

Power Supply

1280W Redundant High-efficiency Digital Power Supplies w/ PMBus 1.2

AC Input	<ul style="list-style-type: none">1000W Output @ 100-140V, 8-12A, 50-60Hz1280W Output @ 180-240V, 6-8A, 50-60Hz
DC Output	<ul style="list-style-type: none">1000W: +12V/83A; +5Vsb/4A1280W: +12V/106.7A, +5Vsb/4A

Certification   Platinum Certified [[Test Report](#)]

System BIOS

BIOS Type	<ul style="list-style-type: none">128Mb SPI Flash EEPROM with AMI BIOS
BIOS Features	<ul style="list-style-type: none">Plug and Play (PnP)APM 1.2PCI 2.2ACPI 1.0 / 2.0USB Keyboard supportSMBIOS 2.3UEFI

Operating Environment / Compliance

RoHS	<ul style="list-style-type: none">RoHS Compliant
Environmental Spec.	<ul style="list-style-type: none">Operating Temperature: 10°C to 35°C (50°F to 95°F)Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)Operating Relative Humidity: 8% to 90% (non-condensing)Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)			
	Part Number	Qty	Description
Motherboard / Chassis	MBD-X9DRT-PIBF	2	Super X9DRT-PIBF Motherboard
	CSE-217HD+-R1K28B	1	2U Chassis
Backplane	BPN-ADP-S3008H-L8IP	2	8 SAS3, 4 SATA2
Backplane	BPN-SAS3-217HD	1	,RoHS/REACH,PBF 2U Twin Backplane, support 24 SAS3/SATA3 HDD (2.5") with Hot Swapping. Per node for 12 HDDs. PWM fan control, HDD spin up and failure LED supported.
Heatsink / Retention	SNK-P0048PS	4	2U Passive CPU Heat Sink for X9, X10 Generation Systems Equipped w/ a Narrow ILM MB