


SuperServer 6028TP-HC0R-SIOM



[▶ Drivers & Utilities](#)
[▶ BIOS](#)
[▶ IPMI](#)
[▶ Tested Memory](#)
[▶ Manuals](#)
[▶ OS Certification Matrix](#)
[▶ Drive Options](#)

Key Features

Four **hot-pluggable** systems (nodes) in a 2U form factor. Each node supports the following:

1. Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 v4[†]/ v3 family; QPI up to 9.6GT/s
2. Up to 2TB[†] ECC 3DS LRDIMM , up to DDR4- 2400[†]MHz ; 16x DIMM slots
3. 1 PCI-E 3.0 x16 (LP), 1 PCI-E 3.0 x8 (LP), 1 **SIOM** card support
4. 1 Dedicated IPMI LAN port
5. 3 Hot-swap 3.5" SAS/SATA HDD Bays
6. LSI 3008 SAS3 controller (8 ports); RAID 0, 1, 10
7. **Mini-mSATA** (half size) support
8. 2000W Redundant Power Supplies Titanium Level (96%)
9. 1 SATA DOM

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

Specifications

Product SKUs	
SYS-6028TP-HC0R-SIOM	<ul style="list-style-type: none"> SuperServer 6028TP-HC0R-SIOM (Black)
Motherboard	
Super X10DRT-PS	
Processor/Cache (per Node)	
CPU	<ul style="list-style-type: none"> Intel® Xeon® processor E5-2600 v4[†]/ v3 family (up to 145W TDP) * Dual Socket R3 (LGA 2011)
Cores / Cache	<ul style="list-style-type: none"> Up to 22 Cores[†] / Up to 55MB[†] Cache
System Bus	<ul style="list-style-type: none"> QPI up to 9.6 GT/s
Note	<ul style="list-style-type: none"> [†] BIOS version 2.0 or above is required
Note	<ul style="list-style-type: none"> * Please contact Supermicro Technical Support for additional information about frequency optimized CPUs and specialized system optimization.

Chassis	
Form Factor	<ul style="list-style-type: none"> 2U Rackmount
Model	<ul style="list-style-type: none"> CSE-827HQ+-R2K04B
Dimensions and Weight	
Width	<ul style="list-style-type: none"> 17.25" (438mm)
Height	<ul style="list-style-type: none"> 3.47" (88mm)
Depth	<ul style="list-style-type: none"> 30.5" (774mm)
Weight	<ul style="list-style-type: none"> Gross Weight: 90 lbs (40.9kg) Net Weight: 72 lbs (32.7 kg)
Available Colors	<ul style="list-style-type: none"> Black
Front Panel	
Buttons	<ul style="list-style-type: none"> Power On/Off button UID button
LEDs	<ul style="list-style-type: none"> Power status LED HDD activity LED Network activity LEDs Universal Information (UID) LED
Expansion Slots (per Node)	

System Memory (per Node)	
Memory Capacity	<ul style="list-style-type: none"> 16x 288-pin DDR4 DIMM slots Up to 2TB[†] ECC 3DS LRDIMM, 512 ECC RDIMM
Memory Type	<ul style="list-style-type: none"> 2400[†]/2133/1866/1600MHz ECC DDR4 SDRAM 72-bit
DIMM Sizes	<ul style="list-style-type: none"> RDIMM: 64GB, 32GB, 16GB, 8GB, 4GB LRDIMM: 64GB, 32GB 3DS LRDIMM: 128GB
Memory Voltage	<ul style="list-style-type: none"> 1.2 V
Error Detection	<ul style="list-style-type: none"> Corrects single-bit errors



On-Board Devices	
Chipset	<ul style="list-style-type: none"> Intel® C612 chipset
SAS	<ul style="list-style-type: none"> LSI 3008 SAS3 (12Gbps) controller; RAID 0, 1, 10 support
IPMI	<ul style="list-style-type: none"> Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support ASPEED AST2400 BMC
Network	<ul style="list-style-type: none"> Must bundle with at least one SIOM network card
Graphics	<ul style="list-style-type: none"> ASPEED AST2400 BMC

Input / Output (per Node)	
SAS	<ul style="list-style-type: none"> 3 SAS3 (12Gbps) ports
LAN	<ul style="list-style-type: none"> 1 RJ45 Dedicated IPMI LAN port
USB	<ul style="list-style-type: none"> 2 USB 3.0 ports total (rear)
VGA	<ul style="list-style-type: none"> 1 VGA port
Serial Port / Header	<ul style="list-style-type: none"> 1 Fast UART 16550 port / 1 Header (internal)
Others	<ul style="list-style-type: none"> 1 SATADOM support on the motherboard

PCI-Express	<ul style="list-style-type: none"> 1 PCI-E 3.0 (x16) Low-profile slot 1 PCI-E 3.0 (x8) Low-profile slot 1 SIOM card support
Note: Must bundle with Network Card	

Drive Bays (per Node)	
Hot-swap	<ul style="list-style-type: none"> 3 Hot-swap 3.5" SAS/SATA HDD trays

System Cooling	
Fans	<ul style="list-style-type: none"> 4x 8cm heavy duty PWM fans with optimal fan speed control

Power Supply (76mm Width)	
2000W Redundant Power Supplies with PMBus	
Total Output Power	<ul style="list-style-type: none"> 1000W/2000W
Dimension (W x H x L)	<ul style="list-style-type: none"> 76 x 40.4 x 336 mm
Input	<ul style="list-style-type: none"> 100-127 Vac / 12-9.5 A / 50-60 Hz 200-220 Vac / 10-9.5 A / 50-60 Hz 220-230 Vac / 10-9.8 A / 50-60 Hz 230-240 Vac / 10-9.8 A / 50-60 Hz 200-240 Vac / 11.8-10 A / 50-60 Hz (UL/cUL only)
+12V	<ul style="list-style-type: none"> Max: 83.3A & Min: 0A (100-127 Vac) Max: 150A & Min: 0A (200-220 Vac) Max: 165A & Min: 0A (220-230 Vac) Max: 166.7A & Min: 0A (230-240 Vac) Max: 166.7A & Min: 0A (200-240 Vac)(UL/cUL only)
+5Vsb	<ul style="list-style-type: none"> Max: 1A / Min: 0A
Output Type	<ul style="list-style-type: none"> 27 Pairs Gold Finger Connector
Certification	  <ul style="list-style-type: none"> UL/cUL/CB/BSMI/CE/CCC Titanium Level [Test Report]

System BIOS	
BIOS Type	<ul style="list-style-type: none"> 128Mb SPI Flash EEPROM with AMI BIOS
BIOS Features	<ul style="list-style-type: none"> Plug and Play (PnP) APM 1.2 PCI 2.2 ACPI 1.0 / 2.0 USB Keyboard support SMBIOS 2.3 UEFI

Operating Environment / Compliance	
RoHS	<ul style="list-style-type: none"> RoHS Compliant
Environmental Spec.	<ul style="list-style-type: none"> Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)			
	Part Number	Qty	Description
Motherboard / Chassis	MBD-X10DRT-PS	4	Super X10DRT-PS Motherboard
	CSE-827HQ+-R2K04B	1	2U Chassis
Air Shroud	MCP-310-21703-0B	4	TwinPo 217HQ+/827HQ+ X10 plastic air shroud,RoHS/REACH
Backplane	BPN-SAS3-827HQ	1	12-port 2U TwinPro^2 SAS3 CSE-827HQ (3 drives per node) backplane, support up to 12x 3.5-inch SAS3/SATA3 HDD/SSD
Backplane	BPN-ADP-S3008L-L6IP	4	LSI 3008, SAS 12Gbs (X6 port inside)
Label	LBL-0108	1	CAUTION LABEL FOR REDUNDANT PWR SYSTEMS
Riser Card	RSC-P-6	4	[NR]RSC-P-6 (1U LHS TwinPro RSC with 1 PCI-Ex16),RoHS
Riser Card	RSC-R1UTP-E16R	4	,RoHS/REACH,PBF
Heatsink / Retention	SNK-P0057PS	4	1U High Performance Passive CPU Heat Sink for X9, X10 Systems Equipped w/ a Narrow ILM MB
Heatsink / Retention	SNK-P0047PSM	4	1U Passive Front CPU Heat Sink w/ a Middle Air Channel for X9, X10 2U Twin^2+ and Twin Pro^2 Series Servers
Power Supply	PWS-2K04A-1R	2	AC-DC 2000W, Titanium Level, Redundancy, 1U, PMBus 1.2, +12V/+5Vsb, 360x76x40mm,HF,RoHS/REACH
Air Shroud	MCP-310-21703-0B or MCP-310-21702-0B	4	TwinPro 217HQ+/827HQ+ X10 plastic air shroud or TwinPro 217HQ+/827HQ+ X10 mylay air shroud
Power Supply	PWS-2K04A-1R or PWS-2K02P-1R	2	2000W Redundant Titanium Level Power Supplies or 2000W Redundant Platinum Level Power Supplies

Optional Parts List			
	Part Number	Qty	Description
Global Services & Support	<u>OS4HR3/2/1</u>	-	3/2/1-year onsite 24x7x4 service
	<u>OSNBD3/2/1</u>	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC	4	OOB Management Package (per node license)
Software	SFT-DCMS-Single	4	DataCenter Management Package (per node license)