

# SuperServer 2029BT-HNTR (Complete System Only)



## Integrated Board



[Super X11DPT-B](#)

Due to the complexity of integration, this product is sold as a completely assembled system only (with minimum 2 CPUs, 2 DIMMs, 1 HDD/NVMe and 1 SIOM card per node). Please contact your Supermicro sales rep for special requirements.

[www.bsicomputer.com](http://www.bsicomputer.com)

[▶ Drivers & Utilities](#) ▶ [BIOS](#) ▶ [IPMI](#) ▶ [Tested Memory](#)  
[▶ Tested M.2 List](#) ▶ [NVMe Options](#) ▶ [Manuals](#) ▶ [Tested SIOM](#) ▶  
[Tested Network Card \(AOC\)](#)

## Key Features

- Hyperscale / Hyperconverged
- Compute Intensive Application
- Data Center, Enterprise, HPC

Four **hot-pluggable** systems (nodes) in a 2U form factor. Each node supports the following:

1. Dual socket P (LGA 3647) supports Intel® Xeon® Scalable Processors, Dual UPI up to 10.4GT/s
2. Up to 3TB ECC 3DS L/RDIMM, up to DDR4-2666MHz; 24 DIMM slots
3. 2 PCI-E 3.0 x16 (LP) slots; 1 [SIOM](#) card support (flexible networking)  
Note: must bundle with Network card
4. IPMI 2.0 + KVM with dedicated LAN
5. 4 Hot-swap 2.5" NVMe/SATA3 + 2 Hot-swap 2.5" SATA3 drive bays; 1 M.2 SATA3 or NVMe support
6. Video via Aspeed AST2500 BMC
7. 4 Heavy duty 8cm PWM fans with air shroud
8. 2200W Redundant Power Supplies Titanium Level (96%)



Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

## Specifications

Product SKUs	
SYS-2029BT-HNTR	▪ SuperServer 2029BT-HNTR (Black)
Motherboard	
<a href="#">Super X11DPT-B</a>	
Processor/Cache (per Node)	
CPU	<ul style="list-style-type: none"> <li>▪ Dual Socket P (LGA 3647)</li> <li>▪ Intel® Xeon® Scalable Processors, Dual UPI up to 10.4GT/s</li> <li>▪ Support CPU TDP 70-205W*</li> </ul>
Cores	▪ Up to 28 Cores with Intel® HT Technology
Note	* 200W/205W CPUs are supported under certain configurations. Please contact Supermicro Technical Support for additional information about specialized system optimization

Chassis	
Form Factor	▪ 2U Rackmount
Model	▪ CSE-217BHQ+ -R2K22BP2
Dimensions and Weight	
Width	▪ 17.6" (447mm)
Height	▪ 3.47" (88mm)
Depth	▪ 28.75" (730mm)
Package	▪ 24.65" (H) x 9.76" (W) x 45.28" (D)
Weight	<ul style="list-style-type: none"> <li>▪ Gross Weight: 85 lbs (38.6kg)</li> <li>▪ Net Weight: 54.5 lbs (24.7 kg)</li> </ul>
Available Colors	▪ Black
Front Panel	
Buttons	<ul style="list-style-type: none"> <li>▪ Power On/Off button</li> <li>▪ UID button</li> <li>▪ Power status LED</li> </ul>

System Memory (per Node)	
Memory Capacity	<ul style="list-style-type: none"> <li>24 DIMM slots</li> <li>Up to 3TB ECC 3DS LRDIMM, 3TB ECC RDIMM, DDR4 up to 2666MHz</li> </ul>
Memory Type	<ul style="list-style-type: none"> <li>2666/2400/2133MHz ECC DDR4 SDRAM</li> </ul>
On-Board Devices	
Chipset	<ul style="list-style-type: none"> <li>Intel® C621 chipset</li> </ul>
Network	<ul style="list-style-type: none"> <li>Must bundle with at least one <a href="#">SIOM</a> network card</li> </ul>
IPMI	<ul style="list-style-type: none"> <li>Support for Intelligent Platform Management Interface v.2.0</li> <li>IPMI 2.0 with virtual media over LAN and KVM-over-LAN support</li> </ul>
Video	<ul style="list-style-type: none"> <li>ASPEED AST2500 BMC</li> </ul>
Input / Output (per Node)	
LAN	<ul style="list-style-type: none"> <li>1 RJ45 Dedicated IPMI LAN port</li> </ul>
USB	<ul style="list-style-type: none"> <li>2 USB 3.0 ports (rear)</li> </ul>
Video	<ul style="list-style-type: none"> <li>1 VGA port</li> </ul>
DOM	<ul style="list-style-type: none"> <li>1 SuperDOM (Disk on Module) port</li> </ul>
System BIOS	
BIOS Type	<ul style="list-style-type: none"> <li>AMI 32Mb SPI Flash ROM</li> </ul>
Management	
Software	<ul style="list-style-type: none"> <li>Intel® Node Manager</li> <li><a href="#">IPMI 2.0</a></li> <li>KVM with dedicated LAN</li> <li><a href="#">SSM</a>, <a href="#">SPM</a>, <a href="#">SUM</a></li> <li><a href="#">SuperDoctor® 5</a></li> <li>Watch Dog</li> </ul>
Power Configurations	<ul style="list-style-type: none"> <li>ACPI / APM Power Management</li> </ul>
PC Health Monitoring	
CPU	<ul style="list-style-type: none"> <li>Monitors for CPU Cores, Chipset Voltages, Memory.</li> <li>4+1 Phase-switching voltage regulator</li> </ul>
FAN	<ul style="list-style-type: none"> <li>Fans with tachometer monitoring</li> <li>Status monitor for speed control</li> <li>Pulse Width Modulated (PWM) fan connectors</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>Monitoring for CPU and chassis environment</li> <li>Thermal Control for fan connectors</li> </ul>

LEDs	<ul style="list-style-type: none"> <li>HDD activity LED</li> <li>Network activity LEDs</li> <li>Universal Information (UID) LED</li> </ul>
Expansion Slots (per Node)	
PCI-Express	<ul style="list-style-type: none"> <li>2 PCI-E 3.0 (x16) Low-profile slots</li> <li>1 <a href="#">SIOM</a> card support (must bundle with network card)</li> </ul>
Drive Bays / Storage (per Node)	
Hot-swap	<ul style="list-style-type: none"> <li>4 Hot-swap 2.5" NVMe/SATA3 + 2 Hot-swap 2.5" SATA3 drive bays</li> </ul>
M.2	<ul style="list-style-type: none"> <li>1 M.2 NVMe or SATA (2280/22110)</li> </ul>
System Cooling	
Fans	<ul style="list-style-type: none"> <li>4 Heavy duty 8cm PWM fans with air shroud</li> </ul>
Power Supply	
2200W Redundant Power Supplies with PMBus	
Total Output Power	<ul style="list-style-type: none"> <li>1200W/1800W/1980W/2090/2200W</li> </ul>
Dimension (W x H x L)	<ul style="list-style-type: none"> <li>45 x 40 x 480 mm</li> </ul>
Input	<ul style="list-style-type: none"> <li>1200W: 100-127Vac / 50-60Hz</li> <li>1800W: 200-220Vac / 50-60Hz</li> <li>1980W: 220-230Vac / 50-60Hz</li> <li>2090W: 230-240Vac / 50-60Hz</li> <li>2090W: 180-220Vac (for UL/cUL only)</li> <li>2200W: 220-240Vac (for UL/cUL only)</li> <li>2090W: 230-240Vdc (for CCC only)</li> </ul>
+12V	<ul style="list-style-type: none"> <li>Max: 100A / Min: 0A (100-127Vac)</li> <li>Max: 150A / Min: 0A (200-220Vac)</li> <li>Max: 165A / Min: 0A (220-230Vac)</li> <li>Max: 174.17A / Min: 0A (230-240Vac)</li> <li>Max: 174.17A / Min: 0A (180-220Vac, UL/cUL only)</li> <li>Max: 183.33A / Min: 0A (220-240Vac, UL/cUL only)</li> <li>Max: 174.17A / Min: 0A (230-240Vdc, CCC only)</li> </ul>
12Vsb	<ul style="list-style-type: none"> <li>Max: 2.1A / Min: 0A</li> </ul>
Output Type	<ul style="list-style-type: none"> <li>Gold Finger</li> </ul>
Certification	  <ul style="list-style-type: none"> <li>UL/cUL/CB/BSMI/CE/CCC Titanium Level [ Cert. in progress ]</li> </ul>
Operating Environment	
RoHS	<ul style="list-style-type: none"> <li>RoHS Compliant</li> </ul>
Environmental Spec.	<ul style="list-style-type: none"> <li>Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F)</li> <li>Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)</li> <li>Operating Relative Humidity: 8% to 90% (non-condensing)</li> <li>Non-operating Relative Humidity: 5% to 95% (non-condensing)</li> </ul>

## Parts List

### Parts List - (Items Included)

Part Number	Qty	Description

Motherboard / Chassis	MBD-X11DPT-B	4	Super X11DPT-B Motherboard 2U Chassis
	CSE-217BHQ+-R2K22BP2	1	
Add-on Card / Module	BPN-ADP-6SATA3H4-1UB	4	Hybrid BPN to support 4 SATA and/or NVMe in addition to 2 SATA ports, HF, RoHS
Backplane	BPN-SAS3-217BHQ-N4	1	2U 4-Node 24-Port Backplane Supports 2x2.5" SATA3/SAS3 SSD/HDD and 4x2.5" SATA3/SAS3/NVMe Storage Media per Node
Drive Tray(s)	MCP-220-00141-0B-BULK	8	Black Gen3 hot-swap 2.5 inch HDD tray with lock improved EMI
Drive Tray(s)	MCP-220-00144-0B-BULK	16	Black Gen3 hot-swap 2.5 inch HDD tray with lock, orange tab
Parts	MCP-240-21730-0N	1	217B BigTwin type I (Impact) BPN retention bkt w/ foam assy
Air Shroud	MCP-310-21712-0B	4	SC217B/827B BigTwin air box for X11DRT-B+
Air Shroud	MCP-310-21718-0B	4	Bigtwin air box for X11DPT-B(4pcs/set)
Manual	MNL-1948-QRG	1	2029BT-H(N/T/NC0)R Quick Reference Guide
Riser Card	RSC-P-6	4	RSC-P-6 (1U LHS TwinPro RSC with 1 PCI-Ex16), RoHS
Riser Card	RSC-R1UTP-E16R	4	1U RHS TwinPro Riser card with one PCI-E x16 slot
Heatsink / Retention	SNK-P0067PS	4	1U Passive CPU Heat Sink for X11 Purley Platform Equipped with a Narrow Retention Mechanism
Heatsink / Retention	SNK-P0067PSM	4	1U Passive CPU Heat Sink with a 26-mm Wide Middle Air Channel for X11 Purley Platform Equipped with a Narrow Retention Mechanism
FAN 1	FAN-0162L4	4	80x80x38 mm, 13.5K RPM, HCP, LMV, and LPC Cooling Fan, RoHS/REACH
Power Supply	PWS-2K22A-1R	2	1U 2200W Redundant Power Supply Titanium, 45(W) X 40(H) X 48
FAN 2	FAN-0183L4	4	80x80x38 mm, 16.5K RPM, Non-hot-swappable Middle Cooling Fan for X11 Twin Pro, X10 and X11 Big Twin Series Servers

#### Optional Parts List

	Part Number	Qty	Description
Global Services & Support	<a href="#">OS4HR3/2/1</a>	-	3/2/1-year onsite 24x7x4 service
	<a href="#">OSNBD3/2/1</a>	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)
SuperDOM	-	-	Supermicro SATA DOM Solutions [ <a href="#">Details</a> ]
Network Card(s)	AOC-S40G-i2Q	-	Standard LP 2-port 40GbE controller, based on Intel Fortville XL710
	AOC-SGP-i2	-	Standard LP, 2x GbE RJ45, PCI-E x4, Intel i350AM2
	AOC-SGP-i4	-	Standard LP, 4x GbE RJ45, PCI-E x4, Intel i350
	AOC-STG-b4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom BCM57840S
	AOC-STGN-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel 82599ES
	AOC-STGN-i1S	-	Standard LP, 1x 10GbE SFP+, PCI-E x8, Intel 82599EN
	AOC-STG-i2T	-	Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel X540
	AOC-STG-i2	-	Standard LP, 2x 10GbE CX4, PCI-E x8, Intel 82598EB