

JBC312U92

NUC Intel i5-4300U Embedded Barebone 2 HDMI 4K / Intel LAN / 1 Serial / 9-24V



Features

- Embedded Barebone System with Planned Lifecycle Through Q2'2019
- Intel Core i5-4300U 1.9GHz Dual-core Processor, Support vPro and RealVNC Viewer Plus Remote Access
- Supports up to 16GB DDR3L-1600 Total Memory
- 2 * HDMI Supporting 4K (3840 x 2160 @30Hz)
- 1 * mSATA Slot, 1 * Serial Port, 3 * USB 3.0
- 1 * Mini-PCIE Slot or 802.11 b/g/n + BT 4.0
- Intel Gigabit LAN, iAMT 9.5, HD Audio
- Watchdog Timer, 9V - 24V DC-In
- Includes Wall, VESA and Din Rail Mounts



Model	<ul style="list-style-type: none"> ■ JBC312U92
Part No	<ul style="list-style-type: none"> ■ HBJC312U92-4300-B (no WIFI) ■ HBJC312U92W-4300UB (with WIFI 802.11 b/g/n)
Processor	<ul style="list-style-type: none"> ■ Intel Core i5-4300U, 1.9GHz, 2.90GHz Burst, Dual-core, Hyper-Threading , Haswell ULT, vPro, Virtualization, 22nm, 15W
Memory	<ul style="list-style-type: none"> ■ 2 * 204-pin DDR3L-1600 SO-DIMM up to 16GB total memory, 1.35V required
Storage	<ul style="list-style-type: none"> ■ 1 * Full-size mSATA slot
Network	<ul style="list-style-type: none"> ■ 1 * Intel i218-LM gigabit LAN supporting iAMT 9.5 & vPro ■ WIFI Model: 802.11 b/g/n + BT 4.0 ■ Non-WIFI Model: 1 * Mini-PCIE slot (half-size)
Other Features	<ul style="list-style-type: none"> ■ HD Audio, AHCI, Watchdog Timer 10-255 min/sec., Kensington lock hole
Rear Panel I/O	<ul style="list-style-type: none"> ■ 2 * USB 3.0 ports, 2 * HDMI, 1 * RJ45, Line-out (w/ Optical-out SPDIF), Antenna holes, Kensington lock hole, 9-24V DC-In
Front Panel I/O	<ul style="list-style-type: none"> ■ Power button, Power LED, 1 * USB 3.0 port, 1 * Serial port (1 * RS232/422/485)
BIOS	<ul style="list-style-type: none"> ■ AMI Flash ROM
Box Contents	<ul style="list-style-type: none"> ■ JBC312U92 Barebone, 36W 12V AC Adapter, US Power Cord, Manual, Drivers, Wall/VESA/DIN Mount, Din Rail Clip, Antenna (WIFI model)
Compliance	<ul style="list-style-type: none"> ■ CE, FCC, RoHS, ErP Ready
Temperature	<ul style="list-style-type: none"> ■ Operating Temperature 0~40 ° C ■ Storage Temperature -20-85 ° C
Dimensions	<ul style="list-style-type: none"> ■ 110 x 116 x 49mm (DxWxH)
OS Support	<ul style="list-style-type: none"> ■ 32/64 bit versions of Win 7, Win 8.1, Win 10, Linux
Warranty	<ul style="list-style-type: none"> ■ 2 Years limited warranty

*Specifications subject to change without notice, not responsible for typographical errors. Does not include memory, HDD, optical, or OS.