

FieldGo C3 Portable Computer

www.bsicomputer.com

SPECIFICATIONS

General Specifications

Standard or micro ATX form factor
Light weight aluminum chassis
Rubber protected corner & drive shock-mount
Add-on card stabilizer
Air circulation fan with filter
LCD brightness control & POWER/IDE LED indicator
Hard Anodizing Surface: MIL-A-8625E Type II/III
Built-in amplified stereo speakers
Mouse touch pad with dual buttons
Soft wheeled carrying case
3 x 8cm fans

Downloads: Technical Drawing (PDF)

Operating Environment

Temperature: 0 to 60°C
Humidity: Meth 5%-95% RH, non-condensing
Altitude: 15,000 ft.
Shock: 15g, 11ms
Vibration: 20-60Hz, 0.075mm
Drop: 3 feet height free drop

LCD Specifications

LCD size: 17.3"
Resolution: 1920×1080
Color: 262K
Brightness: 300 cd/m²
Contrast: 650:1
Response: 6ms

Structure

Total Slots: 7
Full-Lenght: 7
5.25" Bay: 3
Notebook slim CD bay: 1
Dimensions: 17.5" W x 13.5" H x 8.25" D
Weight: 25lbs

Storage Environment

Temperature: -20 to 60°C
Humidity: Meth 5%-95% RH, non-condensing
Altitude: 40,000 ft.
Shock: 50g, 11ms
Vibration: 10-50Hz, 0.15mm
Drop: 3 feet height free drop
EMI & Safety: FCC Class B, CE