

PMS7715 - 15" TFT LCD Fanless Touch Panel PC



Features Highlight

- 15" 1024 x 768 XGA TFT LCD with LED Backlight Fanless Panel PC
- Supports LGA1155 Intel® 3rd Gen. Core™ i5/i3 and Pentium® Processor
- Intel® Q77 Chipset
- 2 x 240-pin 1333/1600MHz DDR3 DIMM Memory (Max. 16GB)
- Support 2 x SATAII HDD or 1 x SATAII HDD + Slim DVD Optical Drive (Optional)
- Support SATA RAID 0, 1, 5, 10
- 4 x USB 3.0 Port, 4 x COM Port, DIO 4-In 4-Out and 1 x Parallel Port
- 2 x PCI Slot Riser Card (Optional)
- 1 x Mini PCIe Slot
- 2 x 10/100/1000Mbps Ethernet LAN Ports
- Built-in VGA and Audio Ports
- 1~255 secs Watchdog Timer Selectable
- IP65 & NEMA 4X Design Stainless Steel Front Bezel



The PMS7715 is a Touch Panel PC comprised of an Intel 3rd Generation Core i5/i3 or Pentium processor and two 240-pin DDR3 DIMM slots for up to 16GB maximum system memory. The front stainless steel front bezel is IP65 rated and houses a 15" LED backlight 400nit LCD with a resolution of 1024 x 768. The touch screen is an ELO 5W Analog resistive type using USB interface. The dimensions of this Panel PC are 402.8 x 303 x 85.8 mm and weighs in at 7.5 kg.

An ATX 220W power supply is standard and offers enough power for the unit and additional peripherals. The PMS7715 is capable of housing two 2.5" SATA HDD and an optional slim DVD. There are two PCI slots (optional) and one 1 x mini PCIe slot available. The I/O interface consists of four USB 3.0, two PS/2 ports, one parallel port and four COM ports. There is also a sound line-in, line-out, MIC in and 4 in / 4 out digital I/O along with two LAN ports and one VGA. The PMS7715 can operate in temperatures ranging from 0° ~ 50°C (32° ~ 122°F).

Broadax Systems, Inc.
17539 E. Rowland Street
City of Industry, CA 91748
Toll Free: 1-800-872-4547
TEL: 626-964-2600
FAX: 626-964-2665
www.bsicomputer.com
info@bsicomputer.com



GS-35F-0496K

PMS7715 - 15" TFT LCD Fanless Touch Panel PC



Specifications


Item No.	PMS7715
Front Bezel	IP65 & NEMA 4X Design Stainless Steel Front Bezel
LCD Size	15" XGA TFT LCD w/ LED Backlight
Touch Screen	5W Analog Resistive (USB Interface)
Resolution	1024 x 768
Brightness(cd/m²)	400 nits
Watchdog	1~255 Secs Watchdog Timer Selectable
Chipset	Q77
CPU Processor	Supports LGA1155 Intel® 3rd Gen. Core™ i5/i3 and Pentium® Processor
System Memory	2 x 240-pin 1333/1600MHz DDR3 DIMM Memory (Max. 16GB)
VGA	1 x VGA
I/O Connector	3 x RS-232, 1 x RS-232/422/485 (COM 3/4 Support +5V, +12V Selectable) 4 x USB 3.0 1 x Parallel port (SPP / EPP / ECP) 1 x Digital I/O (4-In /4-Out) 2 x Gigabit Ethernet LAN
Expansion Slot	1 x Mini PCIe Slot 2 x PCI Slot (Optional)
Keyboard / Mouse	2 x PS/2 Port
Drive Bay	2 x 2.5" HDD or 1 x 2.5" HDD + 1 x Slim DVD Optical Drive (Optional)
Audio	1 x Line in / Line out / Mic in
Power Supply	ATX 220W Power Supply
Mounting	Supports 75 mm / 100 mm VESA Bracket (Optional)
Operation Temperature	32° ~ 122°F (0° ~ 50°C)
Storage Temperature	-4° ~ 176°F (-20° ~ 80°C)
Humidity	20 ~ 90%
Dimensions(WxHxD)	15.86" x 11.93" x 3.38" (402.8 x 303 x 85.8 mm)
Net Weight	16.5 lbs (7.5 Kg)
Certification	CE/ FCC

PMS7715 - 15" TFT LCD Fanless Touch Panel PC

Detail Views

PMS7715 Fanless Touch Panel PC I/O View

1. 1 x RS-232 COM Port
2. VGA Port
3. 6 x USB 2.0
4. 1 x RS-232 COM Port
5. 1 x RS-232 COM Port
6. Power Switch
7. ATX 220W Power Supply
8. 1 x Digital I/O (4-In / 4-Out)
9. 1 x RS-232/422/485 COM Port
10. Audio (Line-in, Line-out and Mic-in)
11. 2 x Gigabit Ethernet
12. 1 x PS/2 Port
13. LPT




PMS7715 Fanless Touch Panel PC Side View

1. 1 x Slim DVD Optical Drive (Optional)



PMS7715 Fanless Touch Panel PC Accessories

1. Support 75 mm / 100 mm VESA Bracket (Optional)



PMS7715 - 15" TFT LCD Fanless Touch Panel PC



Mechanical Drawing

