RMS3335 3U Industrial **Rackmount Computer System**

Specifications

ш				
ш	Chass	10	-09	TITOS
ш	CHASS	13 1		LUI CS

Material of Chassis 1.2mm~2.0mm thickness SGCC ultra-high strength patternless

Standard Color

Front Panel Connector 2 x USB 3.0 Ports

Indicators Power status, HDD, LAN activity LEDs

Front Panel Controls Power On/Off, System Reset

3 x 60mm Cooling Fans with Air Filter (Optional) Cooling Fan

1 x 60mm Fan with Fan Guard Above the Top of I/O Section (Optional)

System Board Size CEB1.01(12"x10.5"), ATX(12"x9.6"), mATX(9.6"x9.6"), ITX(6.7"x6.7")

1 x 5.25" External Drive Bay **Drive Bays** 2 x 2.5" Internal Drive Bays

Expansion Slots 7 x Expansion Slots

Power Supply PS/2 ATX PFC 110/220 VAC Power Supply

Net Weight

Dimension (W x H x D) 19 x 5.25 x 13.2 Inch

Environmental

Operation Temperature 50° to 95°F (Regular Motherboard)

32° to 140°F (Industrial Motherboard)

Non-Operating Temperature

Operating Relative Humidity

Non-Operating Relative Humidity

-40° to 158°F

8% to 90% (non-condensing)

5% to 95% (non-condensing)

