

RMS316 3U Industrial Rackmount Computer System

Specifications

Chassis Form Factor

Standard Color

Front Panel Control

Front Panel Connector

Indicators

System Security

Backplane

Cooling Fan

System Board Form Factor

Drive Bays

Expansion Slots

Power Supply

Net Weight

Dimension (W x H x D)

Operation Temperature

Non-Operating Temperature

Operating Relative Humidity

Non-Operating Relative Humidity

Chassis Features

3U 16-Bay High Density Storage Server
Black/Silver
1 x Power On/Off, 1 x Alarm Mute, 1 x System Reset
2 x USB2.0/3.0 (Option)
LEDs for Power ON/OFF, HDD, LAN, System Alarm
Intrusion Switch
Supports 12Gb/s 16-port Expander Backplane
4 x 80mm Middle Hot-swap Fans with Innovative Anti-vibration Fan Bar; 2 x 60mm Rear Cooling Fans (Optional)

SSI EEB (12" x 13")
16 x 3.5" Hot-swap Drive Bays 1 x Slim Optical Drive 1 x Slim FDD
7 x Full Height and Full Length Slots
1200W Redundant Power Supply

33.48 lbs
17" x 5.2" x 27.93"

Environmental

50° to 95°F (Regular Motherboard)
32° to 140°F (Industrial Motherboard)
-40° to 158°F
8% to 90% (non-condensing)
5% to 95% (non-condensing)

