

RMS3130 - 3U Industrial Rackmount Computer System

Specifications

Material of Chassis

Standard Color

Front Door

Front Panel Connector

Indicators

Speaker

Front Panel Controls

Cooling Fan

Air Filter

System Board Size

Drive Bays

Expansion Slots

Power Supply

Net Weight

Dimension (W x H x D)

Operation Temperature

Non-Operating Temperature

Operating Relative Humidity

Non-Operating Relative Humidity

Chassis Features

1.6mm SECC Zinc-Coated Steel (Military Type)

Black

One Door with 1.6mm SECC Zinc-Coated Steel (Military Type)

2 x USB 2.0 Ports

LEDs for Power ON/OFF, HDD, Fan & Alarm

Built-In 0.4W Speaker

Power ON/OFF, System & Alarm Reset

2 x 60mm, 1 x 40mm

Removeable & Washable

12 x 10 Inch (ATX Form Factor Motherboard)

1 x 5.25" External Drive Bays

1 x 3.5" External Drive Bay

3 x 3.5" Internal Drive Bay

7 Slots

1U PS/2 ATX PFC 110/220 VAC Power Supply

28 lbs

19 x 5.25 x 15 Inch

Environmental

50° to 95°F (Regular Motherboard)

32° to 140°F (Industrial Motherboard)

-40° to 158°F

8% to 90% (non-condensing)

5% to 95% (non-condensing)



RMS3130 - 3U Industrial Rackmount Computer System

Mechanical Drawing

