

PMS1177E - 17" TFT LCD Industrial Touch Panel PC



Specifications

Item No.	PMS1177E
Front Bezel	Industrial-grade Aluminum w/ IP65/NEMA 4 rugged protection
LCD Size	17" SXGA TFT LCD
Touch Screen	5-wire resistive type, Light transmission 79%, 1 million activations (typical) at a single point
Resolution	1280 x 1024 pixels
Brightness(cd/m ²)	380 nits
View Angle(H/V)	170° /160°
Chipset	Intel® C216
CPU Processor	2nd Generation Intel® Core™ i7/ i5/ i3/ Celeron®/ Pentium®/ Xeon® processors
System Memory	2 x 204-pin DDR3 SO-DIMMs (max. 16GB)
I/O Connector	2 x RS-232 1 x RS-232/422/485 with 5V & 12V 1 x RS-232 with 5V & 12V 1 x DVI-I 1 x HDMI 4 x USB 3.0 2 x USB 2.0 2 x 10/100/1000 Mbps Ethernet 1 x Audio (Mic-in/Line-out)
Drive Bay	1 x 3.5" or 2 x 2.5" SATA HDD, 1 x Slim DVD+/-RW Optical Drive(Optional)
Watchdog Timer	255 levels, 1-255 sec.
Audio	Built-in speakers
Wireless Connection	Wireless LAN 802.11 b/g/n Module (Optional)
Expansion Slot	2 x PCIe x8 or 2 x PCI Slots
Power Supply	270W,100 - 240 VAC Power Supply
Operation Temperature	32°F -113°F (0°C-45°C)
Relative Humidity	10%~95% @ 104°F (40°C); non-condensing
Vibration	1.0G, 5-500Hz, random
Dimensions(WxHxD)	16.14" x 13.3" x 4.92" (410 x 338 x 125mm)
Net Weight	18.04 lbs (8.2kg)
EMC	CE

PMS1177E - 17" TFT LCD Industrial Touch Panel PC



Mechanical Drawing

