

PMS1157E - 15" TFT LCD Industrial Touch Panel PC



Features Highlight

- 15" SXGA TFT LCD display
- High performance system supporting LGA1155 socket 3rd & 2nd Generation Intel® Core™ i7/ i5/ i3/ Celeron®/ Pentium®/ Xeon® processors
- Intel® C216 chipset
- Easy installation: a screwless design for user's convenience
- 4 USB 3.0, 2 USB 2.0 and 4 COM ports
- Flexible expansion interface (two PCIe x8 or two PCI slots)
- Built-in speakers and optional Wi-Fi 802.11 b/g/n module
- Robust aluminum with IP 65 compliant front bezel design



The PMS1157E is a multimedia touch panel PC for kiosk application. It has a fashionable mechanism design and industrial-grade material front bezel which can avoid damage from chemical corrosion. To meet the demands of multimedia application, the PMS1157E is powered by a high performance 3rd & 2nd Generation Intel® Core™ i7/ i5/ i3/ Celeron®/ Pentium®/ Xeon® processors with the Intel® C216 Express chipset. It features four COM ports, two Gigabit Ethernet and up to 16 GB memory of dual-channel DDR3 that delivers high computing capability for high performance-demanding applications. The industrial panel PC is most suitable for kiosk, factory and automation.

The PMS1157E supports DVI and HDMI simultaneously that features the use of dual display devices for increasing the area available for programs running on a single computer system. It not only increases larger screen viewing but also improves personal productivity.

The PMS1157E has 2 PCIe x8 or 2 PCI ports for expansion purpose. User can easily plug in standard half-size PCI or PCIe card for any requirement. The PMS1157E features built-in speakers for kiosk application to display multimedia content program. It also supports WLAN module antenna (optional) for wireless network connectivity.

Broadax Systems, Inc.
17539 E. Rowland Street
City of Industry, CA 91748
Toll Free: 1-800-872-4547
TEL: 626-964-2600
FAX: 626-964-2665
www.bsicomputer.com
info@bsicomputer.com



GS-35F-0496K

PMS1157E - 15" TFT LCD Industrial Touch Panel PC



Specifications

Item No.	PMS1157E
Front Bezel	Industrial-grade Aluminum w/ IP65/NEMA 4 rugged protection
LCD Size	15" XGA TFT LCD
Touch Screen	5-wire resistive type, Light transmission 79%, 1 million activations (typical) at a single point
Resolution	1024 x 768 pixels
Brightness(cd/m ²)	350 nits
View Angle(H/V)	160° /140°
Chipset	Intel® C216
CPU Processor	2nd Generation Intel® Core™ i7/ i5/ i3/ Celeron®/ Pentium®/ Xeon® processors
System Memory	2 x 204-pin DDR3 SO-DIMMs (max. 16GB)
I/O Connector	2 x RS-232 1 x RS-232/422/485 with 5V & 12V 1 x RS-232 with 5V & 12V 1 x DVI-I 1 x HDMI 4 x USB 3.0 2 x USB 2.0 2 x 10/100/1000 Mbps Ethernet 1 x Audio (Mic-in/Line-out)
Drive Bay	1 x 3.5" or 2 x 2.5" SATA HDD, 1 x Slim DVD+/-RW Optical Drive(Optional)
Watchdog Timer	255 levels, 1-255 sec.
Audio	Built-in speakers
Wireless Connection	Wireless LAN 802.11 b/g/n Module (Optional)
Expansion Slot	2 x PCIe x8 or 2 x PCI Slots
Power Supply	270W,100 - 240 VAC Power Supply
Operation Temperature	32°F -113°F (0°C-45°C)
Relative Humidity	10%~95% @ 104°F (40°C); non-condensing
Vibration	1.0G, 5-500Hz, random
Dimensions(WxHxD)	14.88" x 12.17" x 4.94" (378 x 309 x 125.5mm)
Net Weight	13.67 lbs (6.2kg)
EMC	CE

PMS1157E - 15" TFT LCD Industrial Touch Panel PC

Detail Views


PMS1157E Industrial Panel PC Front View

1. OSD Sensor



PMS1157E Industrial Panel PC I/O View

1. 1 x RS-232
2. HDMI
3. 4 x USB 3.0
4. Audio (MIC-in/Line-out)
5. 1 x RS-232 (with 5V & 12V)
6. 1 x RS-232
7. 2 x USB 2.0
8. AC plug
9. Power Switch
10. 2 x PCIe x8 or 2 x PCI
11. 2 x GbE LAN
12. DVI-I Port
13. 1 x RS-232/422/485 (with 5V & 12V)



PMS1157E Industrial Panel PC Side View

1. Cooling Fan
2. Slim DVD+/-RW Optical Drive(Optional)



PMS1157E - 15" TFT LCD Industrial Touch Panel PC



Mechanical Drawing

