

PMS1127E - 12.1" TFT LCD Industrial Touch Panel PC



Specifications

Item No.	PMS1127E
Front Bezel	Industrial-grade Aluminum w/ IP65/NEMA 4 rugged protection
LCD Size	12.1" XGA TFT LCD
Touch Screen	5-wire resistive type, Light transmission 79%, 1 million activations (typical) at a single point
Resolution	1024 x 768 pixels
Brightness(cd/m ²)	500 nits
View Angle(H/V)	160° /140°
Chipset	Intel® C216
CPU Processor	2nd Generation Intel® Core™ i7/ i5/ i3/ Celeron®/ Pentium®/ Xeon® processors
System Memory	2 x 204-pin DDR3 SO-DIMMs (max. 16GB)
I/O Connector	1 x RS-232 1 x RS-232/422/485 with 5V & 12V 1 x RS-232 with 5V & 12V 1 x DVI-I 1 x HDMI 4 x USB 3.0 2 x USB 2.0 2 x 10/100/1000 Mbps Ethernet 1 x Audio (Mic-in/Line-out)
Drive Bay	1 x 2.5" SATA HDD.
Watchdog Timer	255 levels, 1~255 sec.
Mounting Kit	VESA & WALL mount kit (Optional)
Wireless Connection	Wireless LAN 802.11 b/g/n Module (Optional)
Expansion Slot	2 x PCIe x8 or 2 x PCI Slots
Power Supply	270W,100 ~ 240 VAC Power Supply
Operation Temperature	32°F -113°F (0°C-45°C)
Relative Humidity	10%~95% @ 104°F (40°C); non-condensing
Vibration	1.0G, 5~500Hz, random
Dimensions(WxHxD)	12.26" x 9.84 " x 4.4" (311.5 x 250 x 111.85mm)
Net Weight	11 lbs (5.0 kg)
EMC	CE

PMS1127E - 12.1" TFT LCD Industrial Touch Panel PC



Mechanical Drawing

