

APPC-1530T - 15" TFT LCD Fanless Touch Panel PC



Specifications

Item No.	APPC-1530T
Front Bezel	IP65 front panel protection Color: Pantone black\RAL 15 00 front bezel w/ Pantone 400C\RAL 090 80 10 metal style membrane
LCD Size	15" TFT LCD with LED Backlight
Touch Screen	5-wire resistive (flush panel type), Light transmission: 80%, Interface: USB
Resolution	1024 x 768 pixels
Brightness(cd/m ²)	400 nits
LCD Color	16.2M
Contrast ratio	700: 1
View Angle(H/V)	160° /140°
CPU Processor	On-board Intel® Atom™ D2550 Dual Core Processor(1M Cache, 1.86 GHz)
Chipset	Intel® NM10 Express chipset
System Memory	2 x 204-pin DDR3 SO-DIMM Memory (max. 4GB)
I/O Connector	1 x Audio (Line-in/ Line-out/ Mic-in) 2 x Gigabit LAN 4 x USB 2.0 2 x RS-232/422/485 1 x VGA Port 1 x PS/2 Keyboard/Mouse 1 x Power Input 1 x External locked CFast socket 1 x Power Switch 1 x Reset button
Drive Bay	1 x 2.5" SATA HDD or 1 x SATA DOM(Optional)
Expansion Slot	2 x Mini-PCIe sockets (Support optional WiFi or 3.5G module)
Wireless	Optional 3.5G / Wi-Fi Module
Watchdog timer	Watchdog timer: Watchdog timeout can be programmed by software from 1 second to 255 seconds and from 1 minute to 255 minutes (Tolerance 15% under room temperature 25°C)
Mounting Kit	Supports Sanel, Wall, Stand, VESA 100mm x 100mm
Power Supply	Power input: 12V- 30V DC 60W AC to DC Power Adaptor (Optional)
Operation Temperature	23°F -140°F (-5°C-60°C)
Relative Humidity	10%~90% relative humidity, non-condensing Limits to be at 90% RH at max 50°C
Vibration	IEC 68 2-64 (w/ HDD) - 1Grms @sine, 5~500Hz, 1hr/axis (HDD Operating) - 2Grms @sine, 5~500Hz, 1hr/axis (CFast Operating) - 2.2Grms @ random condition, 5~500Hz, 0.5hr/axis (Non-operating)
Shock	- IEC 68 2-27 - HDD: 20G@wall mount, half sine, 11ms
Dimensions(WxHxD)	15.13" x 12.2" x 2.49" (384.37 x 309.95 x 63.2mm)
Net Weight	11 lbs (5 Kg)
EMC & Safety	CE approval, FCC Class A

APPC-1530T - 15" TFT LCD Fanless Touch Panel PC



Mechanical Drawing

