

SuperServer 6027TR-D71RF+



Integrated Board



Super X9DRT-HF+

Available Colors:

Black



Key Features

Two **hot-pluggable** systems (nodes) in a 2U form factor. Each node supports the following:

1. Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family†
2. Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
3. 1x MicroLP PCI-E 3.0 x8 slot
4. Intel® i350 Dual port Gigabit Ethernet
5. 6x Hot-swap 3.5" SAS2/SATA3 HDD Bays
6. LSI 2108 SAS2 Controller (BPN-ADP-SAS2-H6iR)
7. 1280W Redundant Power Supplies Platinum Level

Note: Image above may show a varied configuration or optional parts. Please refer to parts list for standard parts included.

Specifications

Product SKUs

SYS-6027TR-D71RF+	■ SuperServer 6027TR-D71RF+ (Black)
-------------------	-------------------------------------

Motherboard

Super X9DRT-HF+

Processor/Cache

CPU	<ul style="list-style-type: none"> ■ Dual Socket R (LGA 2011) ■ Intel® Xeon® processor E5-2600 and E5-2600 v2 family† (up to 135W TDP *)
	* Please contact your Supermicro sales representative for additional details

Note † BIOS version 3.0 or above is required

Cache ■ Up to 30MB

System Bus ■ QPI up to 8 GT/s

System Memory

- 16x 240-pin DDR3 DIMM sockets

Chassis

Form Factor	■ 2U Rackmount
Model	■ CSE-827HD-R1K28MB

Dimensions

Width	■ 17.25" (438mm)
Height	■ 3.47" (88mm)
Depth	■ 28.5" (724mm)
Gross Weight	■ 85 lbs (38.6kg)

Available Colors ■ Black

Front Panel

Buttons	<ul style="list-style-type: none"> ■ Power On/Off button ■ System Reset button ■ UID button
LEDs	<ul style="list-style-type: none"> ■ Power status LED ■ HDD activity LED ■ 2x Network activity LEDs ■ Universal Information (UID) LED

Memory Capacity	<ul style="list-style-type: none"> Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)
Memory Type	<ul style="list-style-type: none"> 1866/1600/1333/1066/800MHz ECC DDR3 SDRAM 72-bit, 240-pin gold-plated DIMMs
DIMM Sizes	<ul style="list-style-type: none"> 32GB, 16GB, 8GB, 4GB, 2GB, 1GB
Memory Voltage	<ul style="list-style-type: none"> 1.5 V, 1.35 V
Error Detection	<ul style="list-style-type: none"> Corrects single-bit errors Detects double-bit errors (using ECC memory)

On-Board Devices

Chipset	<ul style="list-style-type: none"> Intel® C602 Chipset
SAS	<ul style="list-style-type: none"> LSI 2108 SAS2 (6Gbps) w/ Hardware RAID support (BPN-ADP-SAS2-H6iR) RAID 0, 1, 5, 6, 10, 50, 60 support
SATA	<ul style="list-style-type: none"> SATA 2.0 & 3.0 with RAID 0, 1, 5, 10
IPMI	<ul style="list-style-type: none"> Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support Nuvoton WPCM450 BMC
Network Controllers	<ul style="list-style-type: none"> Intel® i350 Dual Port Gigabit Ethernet Virtual Machine Device Queues reduce I/O overhead Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output 1x Realtek RTL8201N PHY (dedicated IPMI)
Graphics	<ul style="list-style-type: none"> Matrox G200eW

Input / Output (per Node)

Serial ATA	<ul style="list-style-type: none"> 6x SATA 3.0 ports (6Gbps)
SAS	<ul style="list-style-type: none"> 6x SAS2 ports (6Gbps)
LAN	<ul style="list-style-type: none"> 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port
USB	<ul style="list-style-type: none"> 5x USB 2.0 ports total (2 rear + 2 via header + 1 Type A)
VGA	<ul style="list-style-type: none"> 1x VGA port
Serial Port / Header	<ul style="list-style-type: none"> 1x Fast UART 16550 port

Expansion Slots (per Node)

PCI-Express	<ul style="list-style-type: none"> 1 Micro Low Profile PCI-E 3.0 x8 slot MicroLP Adapter Matrix
-------------	--

Drive Bays (per Node)

Hot-swap	<ul style="list-style-type: none"> 6x Hot-swap 3.5" SATA/SAS HDD trays
----------	---

System Cooling

Fans	<ul style="list-style-type: none"> 4x 8cm heavy duty PWM fans with optimal fan speed control
------	---

Power Supply

1280W Redundant High-efficiency Digital Power Supplies w/ PMBus 1.2

AC Input	<ul style="list-style-type: none"> 1000W Output @ 100-140V, 12-8A, 50-60Hz 1280W Output @ 180-240V, 8-6A, 50-60Hz
DC Output	<ul style="list-style-type: none"> 1000W: +12V/83A; +5Vsb/4A 1280W: +12V/106.7A, +5Vsb/4A

Certification



Platinum Certified [[Test Report](#)]

System BIOS

BIOS Type	<ul style="list-style-type: none"> 128Mb SPI Flash EEPROM with AMI BIOS
BIOS Features	<ul style="list-style-type: none"> Plug and Play (PnP) APM 1.2 PCI 2.2 ACPI 1.0 / 2.0 USB Keyboard support SMBIOS 2.3 UEFI

Operating Environment / Compliance

RoHS	<ul style="list-style-type: none"> RoHS Compliant
Environmental Spec.	<ul style="list-style-type: none"> Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X9DRT-HF+	2	Super X9DRT-HF+ Motherboard
	CSE-827HD-R1K28MB	1	2U Chassis
Backplane	BPN-ADP-SAS2-H6iR-O-P	2	BPN-ADP-SAS2-H6iR-O-P
Backplane	BPN-SAS-827HD	1	Sup 6x3.5" SATA hdd; hot swap
Heatsink / Retention	SNK-P0048PS	4	2U Passive CPU Heat Sink for X9 Generation Motherboards w/ Narrow ILM
Power Supply	PWS-1K28P-SQ	2	1U 1280W, redundant single output power supply